



LEGRAND* DISJUNCTOR RX3 3P B32 6KA

Descoper? Disjuncteur RX3 3P B32 6kA din categoria Sigurante automate - Tripolare, un produs cu codul 419799. Acesta ofer? caracteristici excelente: Built-in depth 44 mm

Release characteristic B

Number of poles (total) 3

Number of protected poles 3

Rated current 32 A

Rated voltage 400 V

Rated insulation voltage U_i 400 V

Rated impulse withstand voltage U_{imp} 4 kV

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V 10 kA

Voltage type AC

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V 6 kA

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V 10 kA

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V 6 kA

Frequency 50-60 Hz

Current limiting class 3

Flush-mounted installation Yes

Concurrently switching neutral conductor No

Pollution degree 2

Additional equipment possible No

Width in number of modular spacings 3

Degree of protection (IP) IP20

Explosion-proof No

Width 53.4 mm

Height 88.8 mm

Depth 77.3 mm

Degree of impact strength (IK) IK04

Storage temperature -25-60 °C

Nominal voltage 360-440 V

Electric supplying direction By the top or bottom

Terminal marking indication No

Colour Grey

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Busbar and cable

Label space/information surface No

Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficienta si calitate superioara.

Pret: 71,73 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctori-rx3-3p-b32-6ka>