



**LEGRAND* B66LED - BLOC STANDARD - AUTONOMIE 1H CU DIFUZOR
TRANSPARENT - PERMANENT/NEPERMANENT- 450 LM - 1H (LED)**

Descoper? B66LED - Bloc standard - autonomie 1h cu difuzor transparent - Permanent/Nepermanent- 450 lm - 1h (LED) din categoria Corpuri de iluminat - Tehnice, un produs cu codul 661545. Acesta ofer?

caracteristici excelente: Mounting method Wall surface mounted

Function Escape route lighting/signage

Suitable for labelling type Sticker

Type of indicator Single-sided

With pictogram No

Monitoring equipment None

Suitable for standby switching Yes

With remote switch connection No

Supplied remote control No

Power supply system Peripheral (individual battery)

Battery quality NiMH

Lamp type LED not exchangeable

With light source Yes

Lamp holder Other

Number of lighting heads 1

Housing material Plastic

Housing colour Grey

Material cover Plastic, transparent

Voltage type AC

Nominal voltage 230-230 V

Nominal current 200-200 mA

Type of control gear LED operating device current-controlled

Light distributor Diffuser lens/optic/panel

Rated life time L70/B50 at 25 °C 209000 h

Degree of protection (IP) IP66
Degree of impact strength (IK) IK08
Protection class II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 No
Max. system power 45 W
Rated luminous flux according to IEC 62722-2-1 450 lm
Luminous flux in standby mode 0 lm
Colour temperature 5700-5700 K
Nominal operation time 1-1 h
Width 164.5 mm
Height/depth 57 mm
Length 261.2 mm
Number of poles 5
Conductor cross section 2.5 mm²
Connection type Screw connection
Operating / setting temperature -5-35 °C
Storage temperature -10-50 °C
Frequency 50-60 Hz
Mandatory neutral Yes
Terminal marking indication Yes
Halogen free Yes
Terminals capacity 1.5-2.5 mm²
Cable nature for connection Flexible or rigid
Cable support Not applicable
Cable tie suitable with Not applicable
Control mode Wired
Contains Batteries and/or Accumulator Yes
Addressable No
IEC code (Pack1) Cs
Battery ou Accumulator (Pack1) Accumulator (rechargeable)
Element Composition (Pack1) Nickel-Metalhydride
Number of Pack 1 1
Number of Single Element (Pack1) 5
Single Element weight (Pack1) 53 g
Pack1 Location Product includes a battery
Regulation Type (Pack1) I : Industrial (not Portable)
IEC code (Pack2) Cs
Battery ou Accumulator (Pack2) Accumulator (rechargeable)
Element Composition (Pack2) Nickel-Metalhydride
Number of Pack 2 1
Number of Single Element (Pack2) 1
Single Element weight (Pack2) 53 g
Pack2 Location Product includes a battery
Regulation Type (Pack2) I : Industrial (not Portable)
Connected object No. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.
Pret: 967,63 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/b66led-bloc-standard-autonomie-1h-cu-difuzor-transparent-permanent-nepermanent-450-lm-1h-led>