



SCHNEIDER FILTRU IESIRE DV/DT PENTRU UNITATE VITEZA VARIABILA, IP20

Tip produs sau componenta: Dv/dt filter

Compatibilitate gama: Altivar Process ATV900

Easy Altivar 610

Altivar Process ATV600

Altivar Machine ATV340

aplicatie specifica produsului: Filtru de iesire

[In] curent nominal: 15 A

compatibilitate produs: ATV630 variable speed drive wall mount - 3 kW, 380...480 V

ATV630 variable speed drive wall mount - 4 kW, 380...480 V

ATV630 variable speed drive wall mount - 5,5 kW, 380...480 V

ATV630 variable speed drive wall mount - 1,5 kW, 200...240 V

ATV630 variable speed drive wall mount - 2,2 kW, 200...240 V

ATV630 variable speed drive wall mount - 3 kW, 200...240 V

ATV650 variable speed drive wall mount - 3 kW, 380...480 V

ATV650 variable speed drive wall mount - 4 kW, 380...480 V

ATV650 variable speed drive wall mount - 5,5 kW, 380...480 V

ATV610 variable speed drive - 3 kW, 380...415 V

ATV610 variable speed drive - 4 kW, 380...415 V

ATV610 variable speed drive - 5,5 kW, 380...415 V

ATV930 variable speed drive wall mount - 3 kW, 380...480 V

ATV930 variable speed drive wall mount - 4 kW, 380...480 V

ATV930 variable speed drive wall mount - 5,5 kW, 380...480 V

ATV930 variable speed drive wall mount - 1,5 kW, 200...240 V

ATV930 variable speed drive wall mount - 2,2 kW, 200...240 V

ATV930 variable speed drive wall mount - 3 kW, 200...240 V

ATV950 variable speed drive wall mount - 3 kW, 380...480 V

ATV950 variable speed drive wall mount - 4 kW, 380...480 V

ATV950 variable speed drive wall mount - 5,5 kW, 380...480 V

cantitate Incorporata: 1

conexiune electrica: Bloc de conexiuni, capacitate conexiune: 6 mm² / AWG 10

lungimea maxima a cablului motorului: 300 m cablu neecranat

300 m cablu ecranat

dv/dt: 3000 V/ μ s maxim la 200...240 V

3000 V/ μ s maxim la 380...480 V

pierderi termice: 38 W la 4 kHz

maximum drive output frequency: 100 Hz

temperatura ambientală de utilizare: -10...50 °C (f?r? declasarea curentului)

50...60 °C (cu diminuarea curentului cu 1.5% par °C)

altitudinea de functionare: 0...1000 m f?r? declasarea curentului

1000...4000 m cu declasarea curentului cu 1 % pe 100 m

latime: 295 mm

inaltime: 535 mm

adancime: 215 mm

greutate neta: 12 kg

grad de protectie IP: IP20

IP21 (with kit VW3A53902)

temperatura ambientală pentru depozitare: -40...70 °C

Pret: 2.326,76 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/filtru-iesire-dv-dt-pentru-unitate-viteza-variabila-ip20-1>