



SCHNEIDER FILTRU IESIRE DV/DT PENTRU UNITATE VITEZA VARIABILA, IP20

Tip produs sau componenta: Dv/dt filter

Compatibilitate gama: Altivar Process ATV900

Altivar Process ATV600

Easy Altivar 610

Altivar Machine ATV340

aplicatie specifica produsului: Filtru de iesire

[In] curent nominal: 50 A

compatibilitate produs: ATV630 variable speed drive wall mount - 11 kW, 200...240 V

ATV630 variable speed drive wall mount - 15 kW, 380...480 V

ATV630 variable speed drive wall mount - 18,5 kW, 380...480 V

ATV630 variable speed drive wall mount - 22 kW, 380...480 V

ATV650 variable speed drive wall mount - 15 kW, 380...480 V

ATV650 variable speed drive wall mount - 18,5 kW, 380...480 V

ATV650 variable speed drive wall mount - 22 kW, 380...480 V

ATV610 variable speed drive - 18,5 kW, 380...415 V

ATV610 variable speed drive - 22 kW, 380...415 V

ATV630 variable speed drive wall mount - 5,5 kW, 200...240 V

ATV630 variable speed drive wall mount - 7,5 kW, 200...240 V

ATV930 variable speed drive wall mount - 11 kW, 200...240 V

ATV930 variable speed drive wall mount - 15 kW, 380...480 V

ATV930 variable speed drive wall mount - 18,5 kW, 380...480 V

ATV930 variable speed drive wall mount - 22 kW, 380...480 V

ATV950 variable speed drive wall mount - 15 kW, 380...480 V

ATV950 variable speed drive wall mount - 18,5 kW, 380...480 V

ATV950 variable speed drive wall mount - 22 kW, 380...480 V

cantitate Incorporata: 1

conexiune electrica: Bloc de conexiuni, capacitate conexiune: 16 mm² / AWG 6

lungimea maxima a cablului motorului: 500 m cablu neecranat
300 m cablu ecranat
dv/dt: 3000 V/ μ s maxim la 200...240 V
3000 V/ μ s maxim la 380...480 V
pierderi termice: 65 W la 4 kHz
maximum drive output frequency: 100 Hz
temperatura ambientală de utilizare: -10...50 °C (f_r? declasarea curentului)
50...60 °C (cu diminuarea curentului cu 1.5% par °C)
altitudinea de functionare: 0...1000 m f_r? declasarea curentului
1000...4000 m cu declasarea curentului cu 1 % pe 100 m
latime: 300 mm
inaltime: 560 mm
adancime: 245 mm
greutate neta: 18 kg
grad de protectie IP: IP20
IP21 (with kit VW3A53903)
temperatura ambientală pentru depozitare: -40...70 °C
Pret: 4.935,14 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/filtru-iesire-dv-dt-pentru-unitate-viteza-variabila-ip20-2>