



**SCHNEIDER EVLINK, STATIE DE INCARCARE FAST CHARGE PRO DC, 180KW, CU  
DOI CONECTORI CCS2, CABLU 7.5 M**

Gama: EVlink

nume produs: EVlink Pro DC

Tip produs sau componenta: Fast charging station

Tip de instalare: Interior/exterior

descrierea polilor: 3P + N + E

Compatibilitate gama: EVlink Field Services

EVlink (EVlink Load Management System)

aplicatie a dispozitivului: Statie de incarcare vehicul electric

locatie de montare: Floor stand

sistem de impamantare: TN-S

TN-C-S

TT

Sistem IT compatibil cu transf. de izol. suplimentar pe sursa de alim.

[Us] tensiune nominala de alimentare: 380...415 V c.a. la 50...60 Hz, 3 phases + neutral

curent de intrare: 291...323 A

tensiunea nominala de iesire: SAE CCS Combo 2: 180 kW at 1,5...300 A 150...1000 V c.c.

Output type and range: 2 charging cable of 7,5 m

numar de iesiri: 2

tipul conectorului: SAE CCS Combo 2

echipament furnizat: 1 meter display per output

Accuracy class of energy meter: Clasa 1

Accuracy class error of energy meter: 1 % of full scale

tip de protectie: Protectie la scurtcircuit pe iesire

Protectie la suprasarcina

Protectie in caz de defectiune la legatura la pamant

Residual current breaker with overcurrent protection (RCBO)

Protec?ie la cresterea temperaturii  
sistem de control acces: Insigna RFID conformitate cu ISO/IEC 14443 A and B  
Insigna NFC  
tip afisaj: Ecran tactil LCD : 10 inch  
Main user language (constantly evolving): Daneza  
Olandeza  
Engleza  
Franceza  
Germana  
Norwegian  
Spaniola  
tip buton de comanda: Charge interruption button  
material: Cofret stainless steel 304  
Culoare: Parte frontala:signal white (RAL 9003)  
Corpul dispozitivului:negru (Pantone black C)  
eficien??: 94,5 %  
pas de 18 mm: 0,99  
temperatura ambientala de utilizare: -30...50 °C (with derating above 50 °C)  
inaltime: 2103 mm  
latime: 833 mm  
adancime: 963 mm  
greutate produs: 451 kg (without power module)  
541 kg (with power module)  
servicii: Commercial service plan  
Commissioning service  
Warranty extension up to 5 years  
Repair service  
serviciu Ethernet: Web browser  
protocol port de comunicare: OCPP 1.6  
Modbus TCP  
tipul retelei de comunicatie: 4G  
WLAN  
TCP/IP  
Wi-Fi  
compatibilitate electromagnetic?: Imunitate pentru medii industriale  
Emisii standard pentru mediul industrial  
grad de protectie IP: IP55  
grad de protectie IK: IK10  
Screen IK08  
temperatura ambietala pentru depozitare: -40...70 °C  
altitudine de functionare: 0...2000 m  
umiditate relativa: 5...95 %, f?r? condensare  
Standarde: IEC 61851-1:ed. 3  
IEC 61851-23:ed. 1  
IEC 62196-1  
IEC 62196-3  
EN/IEC 61000-6-2:2005  
EN/IEC 61000-6-4:class A  
ISO 15118  
DIN 70121  
Pret: 390.246,70 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/evlink-statie-de-incarcare-fast-charge-pro-dc-180kw-cu-doi-conectori-ccs2-cablu-7-5-m>