



**SCHNEIDER BOBINE DE DECLANSARE LA MINIMA TENSIUNE MN-208 - 277 V 60 HZ,**  
**220 - 240 V 50/60 HZ**

Gama: ComPacT noua generatie

gama de produse: ComPact NSX100...250

ComPacT NSX100...250 noua generatie

ComPact NSX400...630

ComPacT NSX400...630 noua generatie

ComPact NSX100...250 DC

ComPacT NSX100...250 CC noua generatie

ComPact NSX100...250 DC PV

ComPacT NSX100...250 CC PV noua generatie

ComPact NSX400...630 DC

ComPacT NSX400...630 CC noua generatie

ComPact NSX400...630 DC PV

ComPacT NSX400...630 CC PV noua generatie

nume scurt al dispozitivului: MN

Tip produs sau componenta: Declansare la tensiune

aplicatie a dispozitivului: Control

tip tensiune declansare: Bobina de deschidere

Eliberare sub tensiune

tensiune circuit de comanda: 220...240 V c.a. 50/60 Hz

208...277 V c.a. 60 Hz

Compatibilitate gama: ComPacT noua generatie (ComPacT NSX noua generatie)

ComPacT noua generatie (ComPacT NSX CC noua generatie)

Compact (ComPact NSX)

Compact (ComPact NSX DC)

Easypact (EasyPact CVS)

PowerPact (PowerPact Multistandard)

Operating threshold: 0.35...0.7 x Un deschidere

0.85 x Un inchidere

timp de raspuns: 50 ms

putere de mentinere a alimentarii: 5 VA

putere de pornire a alimentarii: 10 VA

terminal auxiliar de conectare: arc 0,5...1,5 mm<sup>2</sup> (AWG 20...AWG 16)

lungimea de dezizolare a cablului: 7 mm

Pret: 414,46 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/bobine-de-declansare-la-minima-tensiune-mn-208-277-v-60-hz-220-240-v-50-60-hz>