



SCHNEIDER INTERFATA SI CONTROLER AUTOMAT - ACP + BA - 380 - 415 V

gama de produse: Compact NS100...630

Masterpact NT

NSX400...630

Compact NS630b...1600

Masterpact NW

NSX100...250

Tip produs sau componenta: Interface and control unit

categorii accesorii / piese de schimb: Accesoriu interblocare

Compatibilitate gama: Compact (ComPact NS) disjunctor

Compact (ComPact NSX) disjunctor

Masterpact (MasterPact NT) disjunctor

Masterpact (Masterpact NW) disjunctor

nume scurt al dispozitivului: ACP + BA

[Us] tensiune de alimentare nominala: 380...415 V c.a. la 50/60 Hz

440 V c.a. la 60 Hz

mod de operare: Operare automata

Oprire (decuplare a sursei normala si de schimb)

Operare fortata de la sursa de schimb

Operare fortata de la sursa normala

dispozitiv de blocare: Masterpact NW

Masterpact NT

NSX100...250

Compact NS630b...1600

NSX400...630

Compact NS100...630

moduri de selectare: Disjunctor pe N

Disjunctor pe R

functie de testare: Prin deschiderea disjuncteurului P25M care alimenteaza controlerul
functie complementara: Transfer voluntar la sursa de schimb (de ex. comenzi de management al energiei)
Contact suplimentar: transfer la sursainloc. numai cand contactul esteinchis
semnalizare locala: Pornit
Declansare defectiune
Oprit
tip de intrare: Contacteaz? clien?ii comand? voit? de transfer pe sursa R
tip de iesire: Contacteaz? clien?ii indicarea func?ion?rii in modul automat sau stop
[Ith] curent termic conventional in aer liber: 8 A
[Ie] curent nominal de utilizare: AC-12 4 A c.a. 440 V
AC-12 5 A c.a. 380/415 V
AC-12 8 A c.a. 110 V
AC-12 8 A c.a. 220/240 V
AC-12 8 A c.a. 24 V
AC-12 8 A c.a. 48 V
AC-13 6 A c.a. 110 V
AC-13 6 A c.a. 220/240 V
AC-13 7 A c.a. 24 V
AC-13 7 A c.a. 48 V
AC-14 4 A c.a. 110 V
AC-14 4 A c.a. 220/240 V
AC-14 5 A c.a. 24 V
AC-14 5 A c.a. 48 V
AC-15 3 A c.a. 220/240 V
AC-15 4 A c.a. 110 V
AC-15 5 A c.a. 24 V
AC-15 5 A c.a. 48 V
DC-12 0,4 A c.c. 250 V
DC-12 0,6 A c.c. 110 V
DC-12 2 A c.c. 48 V
DC-12 8 A c.c. 24 V
DC-13 2 A c.a. 24 V
Compatibilitate produs: Compact NSX100...251
Compact NS630b...1601
Compact NSX400...631
standarde: IEC 947-5-1
grad de protectie IP: IP20 conectori: conforming to SR EN 60529
IP40 fata: conforming to SR EN 60529
IP30 lateral: conforming to SR EN 60529
grad de protectie IK: Fata IK07 conformitate cu EN 50102
Pret: 6.757,39 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/interfata-si-controler-automat-acp-ba-380-415-v>