



SCHNEIDER UNITATE DE AFISARE GRAFICA, 240 X 160 PIXELI

gama de produse: Modicon M221

Tip produs sau componenta: Graphic display

Compatibilitate gama: Modicon M221

consum de curent: 40 mA la 5 V c.c. via RJ45 connector

puterea maxima consumata in W: 1 W

tip afisaj: LCD STN color, retro-iluminat

culoare afisaj: Monochrome

rezolutie afisaj: 240 x 160 pixels

numar de chei: 4 configurable

6 for navigation

standarde: IEC 61131-2

IEC 61010-2-201

certificari produs: cULus

marcaj: CE

locatie de montare: Front cabinet diametru: 22 mm gaura

Bottom of cabinet diametru: 22 mm gaura, conectare prin mounting accessory

tipul conectorului: RJ45 pentru communication and power supply

inaltime: 126 mm

latime: 80 mm

adancime: 63 mm

greutate neta: 0,17 kg

temperatura ambientala de functionare: -15...50 °C

altitudine de functionare: 0...2000 m

altitudinea de depozitare: 0...2000 m

caracteristica de mediu: Corrosive gas free

umiditate relativa: 95 %, fara condensare (transport)

95 %, fara condensare (depozitare)

95 %, fara condensare (functionare)

temperatura ambietala pentru depozitare: -40...70 °C

grad de protectie IP: IP65 parte frontala:

IP20 partea din spate:

grad de poluare: 2 conformitate cu SR EN 60664-1

rezistenta la vibratii: 1.5 mm (f= 3...150 Hz)

2 gn

rezistenta la socuri: 15 gn pentru 11 ms

compatibilitate electromagnetica: Descarcare electrostatic? - test level: 9 kV (descarcare in aer) conforming to IEC 61000-4-2

Descarcare electrostatic? - test level: 4 kV (descarcare pe contact) conforming to IEC 61000-4-2

Test de imunitate la frecventa radio radiata - test level: 10 V/m (80 MHz - 1 GHz) conforming to IEC 61000-4-3

Test de imunitate la frecventa radio radiata - test level: 3 V/m (1.4...2 GHz) conforming to IEC 61000-4-3

Test de imunitate la frecventa radio radiata - test level: 1 V/m (2...3 GHz) conforming to IEC 61000-4-3

Campul magnetic la frecven?a de alimentare - test level: 30 A/m (50/60 Hz) conforming to IEC 61000-4-8

Tranzien?i rapizi/test de imunitate la impulsuri de ionizare - test level: 1 kV conforming to IEC 61000-4-4

Test de imunitate la supratensiuni - test level: 0.5 kV (mod comun) conforming to IEC 61000-4-5

Test de imunitate la supratensiuni - test level: 0.5 kV (mod diferential) conforming to IEC 61000-4-5

Perturba?ii conduse de RF - test level: 10 Vrms (0.15 - 80 MHz) conforming to IEC 61000-4-6

Disturbing field emission - test level: 10...150 kHz (alimentare (c.c.)) conforming to IEC 55011

Disturbing field emission - test level: 120...69 dB μ V/m QP (alimentare (c.c.)) conforming to IEC 55011

Disturbing field emission - test level: 150...1500 kHz (alimentare (c.c.)) conforming to IEC 55011

Disturbing field emission - test level: 1.5...30 kHz (alimentare (c.c.)) conforming to IEC 55011

Disturbing field emission - test level: 30...230 MHz clasa A (10 m) conforming to IEC 55011

Disturbing field emission - test level: 230 MHz...1 GHz clasa A (10 m) conforming to IEC 55011

Disturbing field emission - test level: 79...63 dB μ V/m QP (alimentare (c.c.)) conforming to IEC 55011

Disturbing field emission - test level: 63 dB μ V/m QP (alimentare (c.c.)) conforming to IEC 55011

Disturbing field emission - test level: 40 dB μ V/m QP clasa A (10 m) conforming to IEC 55011

Disturbing field emission - test level: 47 dB μ V/m QP clasa A (10 m) conforming to IEC 55011

Pret: 952,07 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/unitate-de-afisare-grafica-240-x-160-pixeli>