



## SCHNEIDER MODUL ETHERNET PENTRU M580 - 3 PORTURI DE COMUNICATIE ETHERNET -CABLAJ ACOPERIT

gama de produse: Modicon M580

Tip produs sau componenta: Modul de comunicatie

compatibilitate produs: BMEXBP... - Ethernet + X-bus rack

Maximum number of modules per rack: 4

alimentare: Alimentare electrica interna prin rastele

tip de conexiune integrata: 3 Ethernet, tip conector: RJ45, rata de transmisie: 10/100 Mbit/s, mod de transmisie: Ecranat si dublu torsadat

mediu de sustinere a transmisiei: Rack cu Ethernet

serviciu de comunicare: Managementul l?imii de band?

Server FDR

Administrator de retea SNMP

Modbus TCP I/O Scanner and Messaging

Ethernet/IP I/O Scanner and Messaging

RSTP support

Port mirroring

Switch multiport inclus

server Web: Baza

consum de curent: 900 mA la Tensiune alimentare 3.3V c.c. (for product version >= 13)

1800 mA la Tensiune alimentare 3.3V c.c. (for product version < 13)

semnalizare locala: 1 LED (verde) for func?ionare procesor (RUN)

1 LED (rosu) for defect procesor sau sistem(ERR)

1 LED (verde/rosu) for ETH MS (Status configurare port Ethernet)

1 LED (verde/rosu) for Eth NS (Status retea Ethernet)

latime: 32 mm

inaltime: 103,7 mm

lungime: 86 mm

greutate neta: 0,2 kg  
grad de protectie IP: IP20  
tratament protector: Conformal coating  
temperatura ambientala de functionare: 0...60 °C  
marcaj: CE  
certificari produs: UE  
UL  
CSA  
RCM  
EAC  
Certificare navala  
ATEX zona 2/22  
IECEX zone 2/22  
standarde: EN/IEC 61131-2  
EN/IEC 61010-2-201  
UL 61010-2-201  
CSA C22.2 No 61010-2-201  
IACS E10  
EN/IEC 61000-6-5, interface type 1 and type 2  
EN/IEC 61850-3, location G  
Standard EN/IEC 60079-0  
directive: 2014/35/EU - directiva joasa tensiune  
2014/30/EU - directiva de compatibilitate electromagnetica  
2014/34/EU - ATEX directive  
caracteristica de mediu: Gas resistant class Gx conformitate cu ISA S71.04  
Gas resistant class 3C4 conformitate cu IEC 60721-3-3  
Dust resistant class 3S4 conformitate cu IEC 60721-3-3  
Sand resistant class 3S4 conformitate cu IEC 60721-3-3  
Salt resistant nivel 2 conformitate cu IEC 68252  
Mold growth resistant class 3B2 conformitate cu IEC 60721-3-3  
Fungal spore resistant class 3B2 conformitate cu IEC 60721-3-3  
Hazardous location class I division 2  
Pret: 5.990,40 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modul-ethernet-pentru-m580-3-porturi-de-comunicatie-ethernet-cablaj-acoperit>