



**SCHNEIDER UNITATE RACIRE CONECTABILA, MONTAJ PE ACOPERISUL  
DULAPULUI, CLIMASYS CU, 3KW, 3 POLI, 380/460V, 50/60HZ, IP54**

Gama: ClimaSys

nume produs: CU

Suport de montare: Acoperisul cofetului

Tip produs sau componenta: Cooling unit

Installation: Interior roof

destinatie produs: Pentru carcasa

mod de montare: Cu suruburi

Supply Voltage: 380...415 V 3 faze 50 Hz EN/IEC

400/460 V +/- 6 % 3 faze 60 Hz UL

Rated Power: 3200 W

putere de racire: 3200 W 50/60 Hz L35-L35

2640 W 50/60 Hz L35-L50

inaltime: 456 mm

latime: 795 mm

adancime: 575 mm

[In] curent nominal: 3,2 A

curentul de varf: 20 A

puterea consumata in W: 1170 W la 50/60 Hz, L35-L35

1400 W la 50/60 Hz, L35-L50

raportul de eficienta energetica: 2,7

tip de control: Controler electronic

gama de setare a temperaturii: 20...50 °C la 50/60 Hz

temperatura ambientala de utilizare: In cofret 20...50 °C la 50/60 Hz

Outside the enclosure 5...55 °C la 50/60 Hz

Noise level: 72 dB

presiune: 32 bar

Flow rate: Internal circuit 1200 m<sup>3</sup>/h la 50/60 Hz  
External circuit 1400 m<sup>3</sup>/h la 50/60 Hz  
greutate neta: 54,2 kg  
tip de gaz de racire: R134a (0,482 kg)  
Type of filter: Optional external circuit filter  
Recommended circuit breaker protection: M9F23316  
Thermal protection Recommended (fuse): 3 faze 15 A (T)  
material: Otel  
culoare: Gri (RAL 7035)  
certificari produs: UL  
IEC  
EN  
directive: 2006/42/EC - machinery  
2014/30/EU - directiva de compatibilitate electromagnetica  
2011/65/EU - RoHS  
standarde: EN/ISO 12100  
EN 60335-1  
EN 60335-2-40  
EN 61000-3-2  
EN 61000-3-3  
EN 61000-6-2  
EN 61000-6-3  
SR EN IEC 63000:2019  
EN 14511  
grad de protectie IP: IP54 conformitate cu SR EN 60529 (on the internal circuit)  
IP24 conformitate cu SR EN 60529 (on the external circuit)  
Pret: 25.084,23 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/unitate-racire-conectabila-montaj-pe-acoperisul-dulapului-climasys-cu-3kw-3-poli-380-460v-50-60hz-ip54>