



SCHNEIDER MODICON X80 EIO

gama de produse: Modicon X80

Compatibilitate gama: Modicon M580

Tip produs sau componenta: Modul de extensie I/O

aplicatie a dispozitivului: X80 Ethernet RIO drop adaptor

aplicatie specifica produsului: Pentru module I/O la distanta

tip magistrala: Bus X across the remote backplane

Ethernet across the remote backplane

numarul portului: 3

tip de conexiune integrata: 1 port pentru service or distributed equipment

2 port pentru Ethernet RIO Network (RSTP)

tip de retea de comunicatie: IPv4 (internet protocol)

Port protocol de comunicatie: Ethernet/IP

serviciu de comunicare: Adaptor Ethernet/IP

RSTP (Ring topology support)

Ethernet RIO network

Quality of Service (QoS)

CIP Explicit messaging (server)

Modbus TCP server for module diagnostics

Client DHCP

TFTP client

FTP client

FDR client

Client SNTIP

Agent SNMP

cybersecurity: Enable/disable communication ports

Syslog protocol support

tipul conectorului: 3 RJ45

mod de schimb: Half duplex, full duplex, autonegotiation, auto MDIX
rata de transmisie: 10/100 Mbit/s
port Ethernet: 10/100BASE-TX
functie disponibilă: CCOTF (configuration change on the fly)
Input data is collected and published to the remote I/O head adaptor
Output modules are updated with the data received from remote I/O head adaptor
Diagnostics for remote I/O devices (Device DDT)
Port mirroring
System time stamping
Non-interfering type 1
I/O extension rack
inregistrare date: 10 ms time stamps
topologie: Inel
semnalizare locală: 1 LED (verde) for module active (RUN)
1 LED (rosu) for eroare modul (ERR)
1 LED (verde/rosu) for module status (Mod Status)
1 LED (verde/rosu) for network communication status (Net Status)
1 LED (verde) for diagnostic legătură Ethernet (STS)
consum de curent: 1800 mA
tensiune de intrare: 3.3 V c.c.
compatibilitate produs: 0...1024 discrete channel
0...256 analog channel
counter module
time-stamping module
SSI encoder interface module
motion control module
frequency input module
AS-Interface module
serial link module
fiber converter modules
HART module
weighing module
CANopen master module (standalone CPU only)
PROFIBUS module (standalone CPU only)
Ethernet switch module
format de modul: Standard
greutate netă: 0,225 kg
altitudine maximă de transport: 3000 m
Umiditate relativă: 95 % fără condensare
mod de fixare: Cu surub
mod de montare: Montaj rack
latime: 32 mm
inaltime: 100 mm
adancime: 87,5 mm
directive: 2014/35/EU - directiva joasa tensiune
2014/30/EU - directiva de compatibilitate electromagnetica
certificari produs: UE
UL
CSA
RCM
EAC
Certificare navala
standarde: IEC 61131-2
IEC 61010-2-201

UL 61010-2-201

CSA C22.2 No 61010-2-201

IACS E10

IEC 61000-6-5, interface type 1 and type 2

IEC 61850-3, location G

caracteristica de mediu: Mediu standard

grad de protectie IP: IP20

temperatura ambientala de functionare: 0...60 °C

temperatura ambietala pentru depozitare: -40...85 °C

altitudinea de functionare: <= 2000 m

Pret: 5.515,28 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modicon-x80-eio>