

SCHNEIDER MODICON X80 - MODUL DE COM - PT RACK LA DISTANTA ETHERNET RIO M340 - FIX

gama de produse: Modicon X80
Compatibilitate gama: Modicon M580
Modicon Quantum
Tip produs sau componenta: Ethernet I/O head module
aplicatie a dispozitivului: X80 Ethernet RIO drop adaptor
aplicatie specifica produsului: Pentru module I/O la distanta
tip magistrala: Bus X across the remote backplane
numarul portului: 3
tip de conexiune integrata: 1 port pentru service or distributed equipment
2 port pentru Ethernet RIO Network (RSTP)
tip de retea de comunicatie: IPv4 (internet protocol)
Port protocol de comunicatie: Ethernet/IP
serviciu de comunicare: Adaptor Ethernet/IP
RSTP (Ring topology support)
Ethernet RIO network
Quality of Service (QoS)
CIP Explicit messaging (server)
Modbus TCP server for module diagnostics
Client DHCP
TFTP client
FTP client
FDR client
Client SNTP
Agent SNMP
cybersecurity: Enable/disable communication ports
Syslog protocol support

tipul conectorului: 3 RJ45
mod de schimb: Half duplex, full duplex, autonegotiation, auto MDIX
rata de transmisie: 10/100 Mbit/s
port Ethernet: 10/100BASE-TX
functie disponibila: CCOTF (configuration change on the fly)
Input data is collected and published to the remote I/O head adaptor
Output modules are updated with the data received from remote I/O head adaptor
Diagnostics for remote I/O devices (Device DDT)
Port mirroring
System time stamping
Non-interfering type 1
I/O extension rack
inregistrare date: 10 ms time stamps
topologie: Inel
semnalizare locala: 1 LED (verde) for module active (RUN)
1 LED (rosu) for eroare modul (ERR)
1 LED (verde/rosu) for module status (Mod Status)
1 LED (verde/rosu) for network communication status (Net Status)
1 LED (verde) for diagnostic leg?tur? Ethernet (STS)
consum de curent: 1200 mA
tensiune de intrare: 3.3 V c.c.
compatibilitate produs: 0…1024 discrete channel
0…256 analog channel
counter module
time-stamping module
SSI encoder interface module
motion control module
frequency input module
AS-Interface module
serial link module
fiber converter modules
format de modul: Standard
greutate neta: 0,225 kg
altitudine maxima de transport: 3000 m
Umiditate relativa: 95 % f?r? condensare
mod de fixare: Cu surub
mod de montare: Montaj rack
latime: 32 mm
inaltime: 100 mm
adancime: 87,5 mm
tratament protector: Conformal coating
directive: 2014/35/EU - directiva joasa tensiune
2014/30/EU - directiva de compatibilitate electromagnetica
2014/34/EU - ATEX directive
certificari produs: UE
UL
CSA
RCM
EAC
Certificare navala
ATEX zona 2/22
IECEx zone 2/22
Hazardous location class 1, division 2
standarde: IEC 61131-2

IEC 61010-2-201
UL 61010-2-201
CSA C22.2 No 61010-2-201
IACS E10
IEC 61000-6-5, interface type 1 and type 2
IEC 61850-3, location G
IEC 60079-0
UL 121201
Standard CSA C22.2 No 213
caracteristica de mediu: Gas resistant class Gx conformitate cu ISA S71.04
Gas resistant class 3C4 conformitate cu IEC 60721-3-3
Dust resistant class 3S4 conformitate cu IEC 60721-3-3
Sand resistant class 3S4 conformitate cu IEC 60721-3-3
Salt resistant nivel 2 conformitate cu IEC 68252
Mold growth resistant class 3B2 conformitate cu IEC 60721-3-3
Fungal spore resistant class 3B2 conformitate cu IEC 60721-3-3
grad de protectie IP: IP20
temperatura ambientala de functionare: -25…60 °C
temperatura ambietala pentru depozitare: -40…85 °C
altitudinea de functionare: <= 2000 m
Pret: 5.204,81 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/modicon-x80-modul-de-com-pt-rack-la-distanta-ethernet-rio-m340-fix