

SCHNEIDER MODICON X80 RIO DROP E/IP STD

gama de produse: Modicon X80
Compatibilitate gama: Modicon M580
Modicon Quantum
Tip produs sau componenta: Modul de extensie I/O
aplicatie a dispozitivului: X80 Ethernet RIO drop adaptor
aplicatie specifica produsului: Pentru module I/O la distanta
tip magistrala: Bus X across the remote backplane
numarul portului: 2
tip de conexiune integrata: 2 port pentru Ethernet RIO Network (RSTP)
tip de retea de comunicatie: IPv4 (internet protocol)
Port protocol de comunicatie: Ethernet/IP
serviciu de comunicare: Adaptor Ethernet/IP
RSTP (Ring topology support)
Ethernet RIO network
Quality of Service (QoS)
CIP Explicit messaging (server)
Modbus TCP server for module diagnostics
Client DHCP
TFTP client
FTP client
FDR client
Client SNTP
Agent SNMP
cybersecurity: Syslog protocol support
tipul conectorului: 2 RJ45
mod de schimb: Half duplex, full duplex, autonegotiation, auto MDIX
rata de transmisie: 10/100 Mbit/s

port Ethernet: 10/100BASE-TX
functie disponibila: CCOTF (configuration change on the fly)
Input data is collected and published to the remote I/O head adaptor
Output modules are updated with the data received from remote I/O head adaptor
Diagnostics for remote I/O devices (Device DDT)
I/O extension rack
inregistrare date: 10 ms time stamps
topologie: Inel
semnalizare locala: 1 LED (verde) for module active (RUN)
1 LED (rosu) for eroare modul (ERR)
1 LED (verde/rosu) for module status (Mod Status)
1 LED (verde/rosu) for network communication status (Net Status)
1 LED (verde) for diagnostic leg?tur? Ethernet (STS)
consum de curent: 1200 mA
tensiune de intrare: 3.3 V c.c.
compatibilitate produs: 0…128 discrete channel
0…16 analog channel
format de modul: Standard
greutate neta: 0,225 kg
altitudine maxima de transport: 3000 m
Umiditate relativa: 95 % f?r? condensare
mod de fixare: Cu surub
mod de montare: Montaj rack
latime: 32 mm
inaltime: 100 mm
adancime: 87,5 mm
directive: 2014/35/EU - directiva joasa tensiune
2014/30/EU - directiva de compatibilitate electromagnetica
certificari produs: UE
UL
CSA
RCM
EAC
Certificare navala
standarde: IEC 61131-2
IEC 61010-2-201
UL 61010-2-201
CSA C22.2 No 61010-2-201
IACS E10
IEC 61000-6-5, interface type 1 and type 2
IEC 61850-3, location G
caracteristica de mediu: Mediu standard
grad de protectie IP: IP20
temperatura ambientala de functionare: 0…60 °C
temperatura ambietala pentru depozitare: -40…85 °C
altitudinea de functionare: <= 2000 m
Pret: 3.454,09 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/modicon-x80-rio-drop-e-ip-std