



## **SCHNEIDER UNITATE DE FRANARE REZISTIVA - 100 OHM - 100 W - CABLU 3 M - IP65**

gama de produse: Lexium

Altivar

Compatibilitate gama: Lexium 52

Lexium 15

Altivar Machine ATV320

Lexium 32i

Lexium 32

Altivar 32

Easy Altivar 310L

Easy Lexium 16

compatibilitate produs: ATV32H018M2

ATV32H037M2

ATV32H037N4

ATV32H055M2

ATV32H055N4

ATV32H075M2

ATV32H075N4

ATV32HU11N4

ATV32HU15N4

ATV32HU22N4

Variable speed drive ATV320 la 0,18 kW, 200...240 V, o singura faza

Variable speed drive ATV320 la 0,37 kW, 200...240 V, o singura faza

Variable speed drive ATV320 la 0,55 kW, 200...240 V, o singura faza

Variable speed drive ATV320 la 0,75 kW, 200...240 V, o singura faza

Variable speed drive ATV320 la 0,37 kW, 380...500 V, trifazic

Variable speed drive ATV320 la 0,55 kW, 380...500 V, trifazic

Variable speed drive ATV320 la 0,75 kW, 380...500 V, trifazic  
Variable speed drive ATV320 la 1,1 kW, 380...500 V, trifazic  
Variable speed drive ATV320 la 1,5 kW, 380...500 V, trifazic  
Variable speed drive ATV320 la 2,2 kW, 380...500 V, trifazic  
Variable speed drive ATV320 la 0,75 kW, 525...600 V, trifazic  
Variable speed drive ATV320 la 1,5 kW, 525...600 V, trifazic  
Variable speed drive ATV320 la 2,2 kW, 525...600 V, trifazic  
Variable speed drive ATV310L la 0,75 kW  
Variable speed drive ATV310L la 1,5 kW  
Variable speed drive ATV310L la 2,2 kW  
Variable speed drive ATV310L la 3,0 kW  
Variable speed drive ATV310L la 4,0 kW  
Variable speed drive ATV310L la 5,5 kW  
Motion servo drive LXM16D la 0,1 kW, 200...230 V, o singura faza  
Motion servo drive LXM16D la 0,2 kW, 200...230 V, o singura faza  
Motion servo drive LXM16D la 0,4 kW, 200...230 V, o singura faza  
Motion servo drive LXM16D la 0,75 kW, 200...230 V, o singura faza  
Motion servo drive LXM16D la 1 kW, 200...230 V, o singura faza  
Motion servo drive LXM16D la 1,5 kW, 200...230 V, o singura faza  
Tip produs sau componenta: Rezistenta de rupere  
valoare ohmica: 100 Ohm  
varf de energie: 2700 J la 480 V  
3000 J la 400 V  
4500 J la 230 V  
4400 J la 115 V  
putere medie disponibila: 25 W la 50 °C  
putere continua: 100 W  
tip de protectie: Thermal protection via the servo drive  
greutate neta: 0,76 kg  
lungime cablu: 3 m  
grad de protectie IP: IP65  
temperatura ambietala pentru depozitare: -25...85 °C  
temperatura ambietala de functionare: 0...50 °C  
Pret: 1.356,98 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/unitate-de-franare-rezistiva-100-ohm-100-w-cablu-3-m-ip65>