



SCHNEIDER UN BLOC CU 4 CONTACTE AUXILIARE

Tip produs sau componenta: Contact auxiliar

nume scurt al dispozitivului: 4 OF

Compatibilitate gama: Masterpact (Masterpact NW)

Easypact (EasyPact MVS)

Easypact (EasyPact EXE)

compozitie contacte de semnalizare: 4 NO/NC

tip contacte auxiliare: Standard

Nivel scazut

Breaking capacity (A): AC-12: 10 A at 240/380 V c.a. 50/60 Hz conforming to SR EN 60947-2

AC-12: 10 A at 480 V c.a. 50/60 Hz conforming to SR EN 60947-2

AC-12: 6 A at 690 V c.a. 50/60 Hz conforming to SR EN 60947-2

DC-12: 10 A at 24/48 V c.c. conforming to SR EN 60947-2

DC-12: 10 A at 125 V c.c. conforming to SR EN 60947-2

DC-12: 3 A at 250 V c.c. 50/60 Hz conforming to SR EN 60947-2

8 A at 480 V c.a. 50/60 Hz conforming to UL 489

AC-12: 6 A at 600 V c.a. 50/60 Hz conforming to UL 489

6 A at 250 V c.c. conforming to UL 489

sarcina minima: 100 mA la 24 V

2 mA la 15 V

Operation: 600

Duration of operation: 4 min

Operation Description: Assembly and test

Pret: 772,20 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/un-bloc-cu-4-contacte-auxiliare>