



SCHNEIDER SEPARATOR DE SARCINA INTERPACT INS1600 - 1600 A - 4 POLI

Gama: ComPact

nume produs: Compact INS

Tip produs sau componenta: Separator de sarcin?

descriere poli: 4P

Tip retea electrica: C.a.

C.c.

frecventa retea electrica: 50/60 Hz

[Ie] curent nominal de utilizare: AC-21A 1250 A c.a. 50/60 Hz 440/480 V

AC-21A 1250 A c.a. 50/60 Hz 480 V NEMA

AC-21A 1250 A c.a. 50/60 Hz 500/525 V

AC-21A 1250 A c.a. 50/60 Hz 660/690 V

AC-22A 1250 A c.a. 50/60 Hz 440/480 V

AC-22A 1250 A c.a. 50/60 Hz 480 V NEMA

AC-22A 1250 A c.a. 50/60 Hz 500/525 V

AC-22A 1250 A c.a. 50/60 Hz 660/690 V

AC-23A 1250 A c.a. 50/60 Hz 220/240 V

AC-23A 1250 A c.a. 50/60 Hz 380/415 V

AC-23A 1250 A c.a. 50/60 Hz 440/480 V

AC-23A 1250 A c.a. 50/60 Hz 480 V NEMA

AC-23A 1250 A c.a. 50/60 Hz 500/525 V

AC-23A 1250 A c.a. 50/60 Hz 660/690 V

AC-21A 1450 A c.a. 50/60 Hz 220/240 V

AC-21A 1450 A c.a. 50/60 Hz 380/415 V

AC-21B 1600 A c.a. 50/60 Hz 220/240 V

AC-21B 1600 A c.a. 50/60 Hz 380/415 V

AC-21B 1600 A c.a. 50/60 Hz 440/480 V

AC-21B 1600 A c.a. 50/60 Hz 480 V NEMA

AC-21B 1600 A c.a. 50/60 Hz 500/525 V
AC-21B 1600 A c.a. 50/60 Hz 660/690 V
AC-22A 1450 A c.a. 50/60 Hz 220/240 V
AC-22A 1450 A c.a. 50/60 Hz 380/415 V
AC-22B 1600 A c.a. 50/60 Hz 220/240 V
AC-22B 1600 A c.a. 50/60 Hz 380/415 V
AC-22B 1600 A c.a. 50/60 Hz 440/480 V
AC-22B 1600 A c.a. 50/60 Hz 480 V NEMA
AC-22B 1600 A c.a. 50/60 Hz 500/525 V
AC-22B 1600 A c.a. 50/60 Hz 660/690 V
DC-21A 1600 A c.c. 125 V 2 poli in serie
DC-22A 1600 A c.c. 125 V 2 poli in serie
DC-23A 1600 A c.c. 125 V 2 poli in serie
DC-21A 1600 A c.c. 250 V 4 poli in serie
DC-22A 1600 A c.c. 250 V 4 poli in serie
DC-23A 1600 A c.c. 250 V 4 poli in serie
[Ui] tensiune nominala de izolatie: 1000 V c.a. 50/60 Hz
[Uimp] tensiune nominala de tinere la impuls: 12 kV
[Ith] curent termic conventional in aer liber: 1600 A la 60 °C
[Icm] capacitatea nominala de inchidere pe scurtcircuit: 75 kA doar separator de sarcini? 690 V c.a. la 50/60 Hz
330 kA cu intreruptor de protectie in amonte 690 V c.a. la 50/60 Hz
[Ue] tensiune nominala de functionare: 690 V c.a. 50/60 Hz
250 V c.c.
adecvare pentru izolatia: Da
indicator de pozitie contact: Da
separare vizibila: Nu
grad de poluare: 3
tip de control: Manerul rotativ frontal direct
culoare maner: Negru
mod de montare: Fix
suport de montare: Placa
Sina
conexiune superioara: Fata
conexiune inferioara: Fata
putere maxima: AC-23 400 kW la 220/240 V c.a. 50/60 Hz
AC-23 710 kW la 380/400 V c.a. 50/60 Hz
AC-23 800 kW la 415 V c.a. 50/60 Hz
AC-23 900 kW la 500/525 V c.a. 50/60 Hz
dificultate nominala: NeIntrerupt
clasa de dificultate intermitenta: Clasa 120 - 60 %
[Icw] curent nominal de scurtcircuit admisibil: 10 kA in timpul 20 s conformitate cu SR EN 60947-3
20 kA in timpul 3 s conformitate cu SR EN 60947-3
35 kA in timpul 1 s conformitate cu SR EN 60947-3
42 kA in timpul 0.8 s conformitate cu SR EN 60947-3
50 kA in timpul 0.5 s conformitate cu SR EN 60947-3
8 kA in timpul 30 s conformitate cu SR EN 60947-3
durabilitate mecanica: 3000 cic
durabilitate electrica: AC-21A:500 cic 220/240 V c.a. 50/60 Hz
AC-21A:500 cic 380/415 V c.a. 50/60 Hz
AC-21A:500 cic 440/480 V c.a. 50/60 Hz
AC-21A:500 cic 480 V c.a. 50/60 Hz conformitate cu NEMA
AC-21A:500 cic 500/525 V c.a. 50/60 Hz
AC-21A:500 cic 660/690 V c.a. 50/60 Hz

AC-22A:500 cic 220/240 V c.a. 50/60 Hz
AC-22A:500 cic 380/415 V c.a. 50/60 Hz
AC-22A:500 cic 440/480 V c.a. 50/60 Hz
AC-22A:500 cic 480 V c.a. 50/60 Hz conformitate cu NEMA
AC-22A:500 cic 500/525 V c.a. 50/60 Hz
AC-22A:500 cic 660/690 V c.a. 50/60 Hz
DC-21A:500 cic 125 V c.c. 2 poli in serie
DC-22A:500 cic 125 V c.c. 2 poli in serie
DC-21A:500 cic 250 V c.c. 4 poli in serie
DC-22A:500 cic 250 V c.c. 4 poli in serie
AC-21B:100 cic 220/240 V c.a. 50/60 Hz
AC-21B:100 cic 380/415 V c.a. 50/60 Hz
AC-21B:100 cic 440/480 V c.a. 50/60 Hz
AC-21B:100 cic 480 V c.a. 50/60 Hz conformitate cu NEMA
AC-21B:100 cic 500/525 V c.a. 50/60 Hz
AC-21B:100 cic 660/690 V c.a. 50/60 Hz
AC-22B:100 cic 220/240 V c.a. 50/60 Hz
AC-22B:100 cic 380/415 V c.a. 50/60 Hz
AC-22B:100 cic 440/480 V c.a. 50/60 Hz
AC-22B:100 cic 480 V c.a. 50/60 Hz conformitate cu NEMA
AC-22B:100 cic 500/525 V c.a. 50/60 Hz
AC-22B:100 cic 660/690 V c.a. 50/60 Hz
AC-23B:500 cic 220/240 V c.a. 50/60 Hz
AC-23B:500 cic 380/415 V c.a. 50/60 Hz
AC-23B:500 cic 440/480 V c.a. 50/60 Hz
AC-23B:500 cic 480 V c.a. 50/60 Hz conformitate cu NEMA
AC-23B:500 cic 500/525 V c.a. 50/60 Hz
AC-23B:500 cic 660/690 V c.a. 50/60 Hz
DC-23B:500 cic 125 V c.c. 2 poli in serie
DC-23B:500 cic 250 V c.c. 4 poli in serie
pasul conexiunii: 70 mm
inaltime: 300 mm
latime: 410 mm
adancime: 146,5 mm
greutate neta: 18 kg
standarde: SR EN 60947-3
IEC 60947-1
certificari produs: KEMA-KEUR
grad de protectie IP: IP40 conforming to SR EN 60529
grad de protectie IK: IK07 conforming to EN 50102
temperatura ambientala de functionare: -25...70 °C
temperatura ambietala pentru depozitare: -50...85 °C
Pret: 12.994,32 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/separator-de-sarcina-interpact-ins1600-1600-a-4-poli>