



**SCHNEIDER INTERFATA TACTILA, SPACELOGIC, ADVANCED DISPLAY V3, AFISAJ  
HMI DE NALTA REZOLUTIE DE 10,1", PENTRU AS/AS-B/AS-P, IP54, 24 V CA SI CC**

sistem de operare: Android 8.1  
adancime de montaj: 15,2 mm  
inaltime: 195,6 mm  
material carcasa: ABS/PC  
Gama: SpaceLogic  
temperatura ambietala pentru depozitare: -20...60 °C  
adancime: 25 mm  
consum de curent: 1.27 A  
Rezistenta la foc: UL94-V0  
latime: 258 mm  
mod de montare: Panel-mounted  
certificari produs: UE  
FCC  
UL 60950  
RCM  
greutate neta: 0,933 kg  
Tip produs sau componenta: HMI  
culoare: Alb  
[In] curent nominal: 1 A  
tip afisaj: TFT LCD touchscreen  
dimensiune afisaj: 10.1 inch  
temperatura ambietala de functionare: 0...40 °C  
rezolutie afisaj: 1280 x 800 pixels  
tipul retelei de comunicatie: IEEE 802.11 b/g/n at 2.4 GHz  
[Us] tensiune de alimentare nominala: 24 V c.a. +/- 10 %  
24 V c.c. +/- 10 %

Compatibilitate gama: SpaceLogic AS  
SpaceLogic AS-P  
SpaceLogic AS-B  
Standarde: EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013  
IEC 60950-1:ed. 2:2005+Am1:2009+Am2:2013  
UL 60950-1:ed. 2:2014  
CSA C22.2 No. 60950-1-07:ed. 2:2014  
EN 55024:2010  
FCC part 15 Subpart B class B  
Umiditate relativa: 0...95 % RH, fara condensare  
numarul portului: 1, tip conector: USB tip C  
nume procesor: Intel Celeron N3350 dual core at 1,1 GHz  
tip memorie: 2 GB RAM  
Communication port protocol: USBNet: USB 2.0  
alimentare: External power supply  
grad de protectie IP: IP54  
Pret: 9.031,20 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/interfata-tactila-spacelogic-advanced-display-v3-afisaj-hmi-de-nalta-rezolutie-de-10-1-pentru-as-as-b-as-p-ip54-24-v-ca-si-cc>