



SCHNEIDER MODUL PREVENTA CAT.4 CARACTERISTICI XPSUAF + PNP/NPN, 24VAC/DC SURUB

gama de produse: Harmony Safety Automation

Tip produs sau componenta: Modul de siguranta

nume modul de siguranta: XPSUAK

aplicatie modul de siguranta: Monitoring antivalent contacts

For emergency stop, guard and light curtain monitoring

Monitoring of pressure-sensitive 4-wire protective devices

functie a modulului: Buton de oprire de urgenta cu 2 contacte NC

Guard monitoring with 1 or 2 limit switches

Monitoring 2 PNP sensors

Magnetic switch monitoring

Light curtain monitoring

RFID switch

Monitorizare a echipamentelor de protectie electro-sensibil (ESPE)

Sensing mat/edges

Monitorizare senzor de proximitate

Monitoring 1 PNP + 1 NPN sensor

nivel de securitate: Poate ajunge la PL e/categoria 4 for normally open relay contact conformitate cu ISO 13849-1

Poate atinge SILCL 3 for normally open relay contact conformitate cu IEC 62061

Poate ajunge la SIL 3 for normally open relay contact conformitate cu IEC 61508

Can reach PL c/category 1 for normally closed relay contact conformitate cu ISO 13849-1

Poate atinge SILCL 1 for normally closed relay contact conformitate cu IEC 62061

Can reach SIL 1 for normally closed relay contact conformitate cu IEC 61508

fiabilitatea datelor despre securitate: MTTFd > 30 years conformitate cu ISO 13849-1

Dcavg >= 99 % conformitate cu ISO 13849-1

PFHd = 1.13E-09 conformitate cu ISO 13849-1

HFT = 1 conformitate cu IEC 62061
PFHd = 1.13E-09 conformitate cu IEC 62061
SFF > 99% conformitate cu IEC 62061
HFT = 1 conformitate cu IEC 61508-1
PFHd = 1.13E-09 conformitate cu IEC 61508-1
SFF > 99% conformitate cu IEC 61508-1
Type = B conformitate cu IEC 61508-1
tip circuit electric: NC pair
PNP pair
Antivalent pair
OSSD pair
conexiuni - borne: Cutie de borne cu suruburi amovibile, 0.2...2.5 mm² rigid sau flexibil
Cutie de borne cu suruburi amovibile, 0.25...2.5 mm² flexibil cu pin un singur conductor
Cutie de borne cu suruburi amovibile, 0.2...1.5 mm² rigid sau flexibil conductor dublu
Cutie de borne cu suruburi amovibile, 2 x 0.25...1 mm² flexibil cu pin without cable end, with bezel
Cutie de borne cu suruburi amovibile, 2 x 0.5...1.5 mm² flexibil cu pin cu pini cu guler
[Us] tensiune de alimentare nominala: 24 V c.a. - 15...10 %
24 V c.c. - 20...20 %
timp de sincronizare intre intrari: 0,5 s
2 s
4 s
tip de pornire: Automatic/manual/monitored
puterea consumat? in W: 2,0 W 24 V c.c.
puterea consumat? in VA: 5,0 VA 24 V c.a. 50/60 Hz
tip de protectie intrare: Intern, electronic
safety outputs: 2 NO + 1 NC
safety inputs: 2 safety input 24 V c.c. 5 mA
maximum wire resistance: 500 Ohm
compatibilitate intrare: Normally closed circuit conformitate cu ISO 14119
Limitatoare XC conformitate cu ISO 14119
Contact mecanic conformitate cu ISO 14119
Normally closed circuit conformitate cu ISO 13850
Antivalent pair conformitate cu ISO 14119
OSSD pair conformitate cu IEC 61496-1-2
Senzori de proximitate PNP 3 fire
[Ie] curent nominal de utilizare: 5 A AC-1 for normally open relay contact
3 A AC-15 for normally open relay contact
5 A DC-1 for normally open relay contact
3 A DC-13 for normally open relay contact
3 A AC-1 for normally closed relay contact
1 A AC-15 for normally closed relay contact
3 A DC-1 for normally closed relay contact
1 A DC-13 for normally closed relay contact
control outputs: 3 pornit/oprit configurable pulsed output
tipul intr?rii/ie?irii: Semiconductor pulsed diagnostic output 24 V c.c., 20 mA Z1, not safety-related
[Ith] curent termic conven?ional in aer liber: 8 A
calibrul fuzibilului asociat: 10 A gG pentru circuit de ie?ire pe releu NO conformitate cu IEC 60947-1
curent minim de iesire: 10 mA pentru ie?ire releu
tensiune minima de iesire: 12 V pentru ie?ire releu
[Ui] tensiune nominala de izolatie: 250 V (grad de poluare 2) conformitate cu IEC 60947-1
[Uimp] tensiune de tinere la impuls: 4 kV categorie de supratensiune II conformitate cu IEC 60947-1
suport de montare: Sina DIN simetrica, 35 mm
adancime: 120 mm
inaltime: 100 mm

latime: 22,5 mm

greutate neta: 0,200 kg

temperatura ambientala de functionare: -25...55 °C

standarde: SR EN 60947-5-1

IEC 61508-1 functional safety standard

IEC 61508-2 functional safety standard

IEC 61508-3 functional safety standard

IEC 61508-4 functional safety standard

IEC 61508-5 functional safety standard

IEC 61508-6 functional safety standard

IEC 61508-7 functional safety standard

ISO 13849-1 functional safety standard

IEC 62061 functional safety standard

certificari produs: TUV

cULus

grad de protectie IP: IP20 (borne) conformitate cu SR EN 60529

IP40 (carcas?) conformitate cu SR EN 60529

IP54 (mounting area) conformitate cu SR EN 60529

Umiditate relativa: 5...95 % fara condensare

Pret: 862,32 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/modul-preventa-cat-4-caracteristici-xpsuaf-pnp-npn-24vac-dc-surub>