



SCHNEIDER MODICON X80 - MODUL 4 IES ANA IZOLATE - FIX

gama de produse: Modicon X80

Tip produs sau componenta: Modul de iesire analogic

aplicatie specifica produsului: Pentru mediu greu

conexiune electrica: 20 cai 1 conector

Isolation between channels: Izolat

eroare de masurare: 0.1 % din scala complet? 25 °C

≤ 0.45 % of full scale - 25...70 °C

abatere a temperaturii: 45 ppm/°C +/- 10 V

45 ppm/°C 0...20 mA

45 ppm/°C 4...20 mA

Minimum crosstalk attenuation: 80 dB

Atenuare zgomot EMI/RFI (de la 100 kHz la 10 mHz): 100 dB

tensiunea de izolatie: 1400 V c.c. between channels and ground

1400 V c.c. between channels and bus

750 V c.c. between channels

tip detec?ie: Open circuit 0...20 mA

Open circuit 4...20 mA

Short circuit +/- 10 V

impedanta ohmica a sarcinii: ≥ 1000 Ohm +/- 10 V

≤ 500 Ohm 0...20 mA

≤ 500 Ohm 4...20 mA

nivel de iesire: Nivelinalt

numarul iesirii analogice: 4

tip iesire analogica: Curent 0...20 mA

Curent 4...20 mA

Tensiune +/- 10 V

rezolutie de iesire analogica: 16 bi?i + semn

alimentare: Alimentare electrica interna prin rastel
timp de conversie: ≤ 1 ms
valoarea maxima a conversiei: 0...21 mA 0...20 mA
0...21 mA 4...20 mA
+/- 10.5 V +/- 10 V
mod revenire: Configurabil
Predefinit
siguranta MTBF: 1000000 H
altitudinea de functionare: 0...2000 m
2000...5000 m cu
stare LED: 1 LED (verde) RUN
1 LED per canal (verde) diagnostic canal
1 LED (rosu) ERR
1 LED (rosu) I/O
greutate neta: 0,15 kg
puterea consumat? in W: 3 W 24 V c.c. typical
3,6 W 24 V c.c. maxim
0,45 W 3.3 V c.c. typical
0,51 W 3.3 V c.c. maxim
consum de curent: 150 mA la 3.3 V c.c.
140 mA la 24 V c.c.
rezistenta la vibratii: 3 gn
rezistenta la socuri: 30 gn
temperatura ambietala pentru depozitare: -40...85 °C
temperatura ambiental de functionare: -25...70 °C
umiditate relativa: 5...95 % la 55 °C f?r? condensare
grad de protectie IP: IP20
directive: 2014/35/EU - directiva joasa tensiune
2014/30/EU - directiva de compatibilitate electromagnetica
certificari produs: UE
RCM
CSA
EAC
Certificare navala
UL
ATEX
IEC-Ex
standarde: EN/IEC 61010-2-201
EN/IEC 61131-2
UL 61010-2-201
CSA C22.2 No 61010-2-201
caracteristica de mediu: Gas resistant class Gx
Gas resistant class 3C4
Dust resistant class 3S4
Sand resistant class 3S4
Salt resistant nivel 2
Mold growth resistant class 3B2
Fungal spore resistant class 3B2
Hazardous location
tratament protector: Conformal coating
Pret: 3.376,37 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modicon-x80-modul-4-ies-ana-izolate-fix>