



### SCHNEIDER MODUL ETHERNET / SERIAL RTU - 2 X RJ45

gama de produse: Modicon M340

Tip produs sau componenta: Modul de comunicare

tip de conexiune integrata: Ethernet RJ45 10/100 Mbit/s 1 pereche torsadata transparent ready clasa C30

Serial RS232/485 RJ45 300/38400 bit/s 1 pereche torsadata transparent ready clasa C30

tratament protector: Conformal coating

serviciu de comunicare: Managementul l?imii de band?

Mesagerie TCP Modbus

DNP3/DNP3 IP protocol

IEC 60870-5 -101/-104 protocol

Time stamped events management

External modem management (serial, PSTN, GSM, GPRS/3G)

Data logging in CSV files

Email/SMS notifications

Web server, rack viewer, data editor

BootP, DHCP, FDR client

SMTP server, FTP client/server, NTP client, SNMP agent,

Automatic events backup on power loss

Multi-protocols support in a single module (master and slave)

Transparent events routing from remote slaves to SCADA

port Ethernet: 10BASE-T/100BASE-TX

descriere memorie: Supplied Flash SD memory card (BMXRWS128MWF) 128000 kB

memorie utilizata: Activarea serverului standard de web

User web pages storage

Data logging CSV files storage

alimentare: Alimentare electrica interna prin rastel

semnalizare locala: 1 LED (verde) for activitate in re?eaua Ethernet (ETH ACT)

1 LED (verde) for func?ionare procesor (RUN)

1 LED (verde) for starea re?elei Ethernet (ETH STS)  
1 LED (rosu) for defect card de memorie (CARD ERR)  
1 LED (rosu) for defect procesor sau sistem(ERR)  
1 LED (rosu) for Descarcare in curs ()  
1 LED (galben) for serial communication (SER COM)  
1 LED (verde) for data rate (ETH LINK)  
consum de curent: 95 mA la 24 V c.c.  
format de modul: Standard  
greutate neta: 0,2 kg  
temperatura ambientala de functionare: -25...70 °C  
Umiditate relativa: 10...95 % f?r? condensare  
grad de protectie IP: IP20  
directive: 2014/35/EU - directiva joasa tensiune  
2014/30/EU - directiva de compatibilitate electromagnetica  
2014/34/EU - ATEX directive  
certificari produs: UE  
UL  
CSA  
RCM  
EAC  
Certificare navala  
ATEX zona 2/22  
IECEX zone 2/22  
UKCA  
standarde: EN/IEC 61131-2  
EN/IEC 61010-2-201  
UL 61010-2-201  
CSA C22.2 No 61010-2-201  
IACS E10  
EN/IEC 61000-6-5, interface type 1 and type 2  
EN/IEC 61850-3, location G  
Standard EN/IEC 60079-0  
caracteristica de mediu: Gas resistant class Gx conformitate cu ISA S71.04  
Gas resistant class 3C4 conformitate cu IEC 60721-3-3  
Dust resistant class 3S4 conformitate cu IEC 60721-3-3  
Sand resistant class 3S4 conformitate cu IEC 60721-3-3  
Salt resistant nivel 2 conformitate cu IEC 68252  
Mold growth resistant class 3B2 conformitate cu IEC 60721-3-3  
Fungal spore resistant class 3B2 conformitate cu IEC 60721-3-3  
Hazardous location class I division 2  
Pret: 6.062,26 LEI (TVA inclus)

Detalii online: <https://www.materialeelectronice.ro/modul-ethernet-serial-rtu-2-x-rj45>