

SCHNEIDER MODUL ETHERNET / SERIAL RTU - 2 X RJ45

gama de produse: Modicon M340
Tip produs sau componenta: Modul de comunicatie
tip de conexiune integrata: Ethernet RJ45 10/100 Mbit/s 1 pereche torsadata transparent ready clasa C30
Serial RS232/485 RJ45 300/38400 bit/s 1 pereche torsadata transparent ready clasa C30
tratament protector: Conformal coating
serviciu de comunicare: Managementul l??imii de band?
Mesagerie TCP Modbus
DNP3/DNP3 IP protocol
IEC 60870-5 -101/-104 protocol
Time stamped events management
External modem management (serial, PSTN, GSM, GPRS/3G)
Data logging in CSV files
Email/SMS notifications
Web server, rack viewer, data editor
BootP, DHCP, FDR client
SMTP server, FTP client/server, NTP client, SNMP agent,
Automatic events backup on power loss
Multi-protocols support in a single module (master and slave)
Transparent events routing from remote slaves to SCADA
port Ethernet: 10BASE-T/100BASE-TX
descriere memorie: Supplied Flash SD memory card (BMXRWS128MWF) 128000 kB
memorie utilizata: Activarea serverului standard de web
User web pages storage
Data logging CSV files storage
alimentare: Alimentare electrica interna prin rastel
semnalizare locala: 1 LED (verde) for activitate in re?eaua Ethernet (ETH ACT)
1 LED (verde) for func?ionare procesor (RUN)

1 LED (verde) for starea re?elei Ethernet (ETH STS)
1 LED (rosu) for defect card de memorie (CARD ERR)
1 LED (rosu) for defect procesor sau sistem(ERR)
1 LED (rosu) for Descarcare in curs ()
1 LED (galben) for serial communication (SER COM)
1 LED (verde) for data rate (ETH LINK)
consum de curent: 95 mA la 24 V c.c.
format de modul: Standard
greutate neta: 0,2 kg
temperatura ambientala de functionare: -25…70 °C
Umiditate relativa: 10…95 % f?r? condensare
grad de protectie IP: IP20
directive: 2014/35/EU - directiva joasa tensiune
2014/30/EU - directiva de compatibilitate electromagnetica
2014/34/EU - ATEX directive
certificari produs: UE
UL
CSA
RCM
EAC
Certificare navala
ATEX zona 2/22
IECEx zone 2/22
UKCA
standarde: EN/IEC 61131-2
EN/IEC 61010-2-201
UL 61010-2-201
CSA C22.2 No 61010-2-201
IACS E10
EN/IEC 61000-6-5, interface type 1 and type 2
EN/IEC 61850-3, location G
Standard EN/IEC 60079-0
caracteristica de mediu: Gas resistant class Gx conformitate cu ISA S71.04
Gas resistant class 3C4 conformitate cu IEC 60721-3-3
Dust resistant class 3S4 conformitate cu IEC 60721-3-3
Sand resistant class 3S4 conformitate cu IEC 60721-3-3
Salt resistant nivel 2 conformitate cu IEC 68252
Mold growth resistant class 3B2 conformitate cu IEC 60721-3-3
Fungal spore resistant class 3B2 conformitate cu IEC 60721-3-3
Hazardous location class I division 2
Pret: 6.118,77 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/modul-ethernet-serial-rtu-2-x-rj45