

SCHNEIDER CONTACTOR TESYS D - 3P -= 440 V - 38 A AC-3 - 100 - 250 V C.A/C.C BOBINA

gama de produse: TeSys Deca Advanced
Tip produs sau componenta: Contactor
nume scurt al dispozitivului: LC1D
aplicatie contactor: Comanda motor
Sarcina rezistiva
categorie de utilizare: AC-1
AC-3
AC-3e
descriere poli: 3P
[Ue] tensiune nominala de functionare: Circuit de alimentare <= 690 V c.a. 25...400 Hz
[Ie] curent nominal de utilizare: 50 A (at 38 A (at 38 A (at [Uc] control circuit voltage: 100...250 V c.a. 50/60 Hz
100...250 V c.c.
putere motor kW: 9 kW at 220...230 V c.a. 50 Hz (AC-3)
18,5 kW at 380...400 V c.a. 50 Hz (AC-3)
18,5 kW at 415 V c.a. 50 Hz (AC-3)
18,5 kW at 440 V c.a. 50 Hz (AC-3)
18,5 kW at 500 V c.a. 50 Hz (AC-3)
18,5 kW at 660...690 V c.a. 50 Hz (AC-3)
9 kW at 220...230 V c.a. 50 Hz (AC-3e)
18,5 kW at 380...400 V c.a. 50 Hz (AC-3e)
18,5 kW at 415 V c.a. 50 Hz (AC-3e)
18,5 kW at 440 V c.a. 50 Hz (AC-3e)
18,5 kW at 500 V c.a. 50 Hz (AC-3e)
18,5 kW at 660...690 V c.a. 50 Hz (AC-3e)
putere motor hp: 2 CP at 115 V c.a. 60 Hz for 1 faz? motors

5 CP at 230/240 V c.a. 60 Hz for 1 faz? motors
10 CP at 200/208 V c.a. 60 Hz for 3 faze motors
10 CP at 230/240 V c.a. 60 Hz for 3 faze motors
20 CP at 460/480 V c.a. 60 Hz for 3 faze motors
25 CP at 575/600 V c.a. 60 Hz for 3 faze motors
Cod compatibilitate: LC1D
compozitie contact pol: 3 NO
capac de protectie: Cu
[Ith] curent termic conventional in aer liber: 10 A (at 60 °C) for circuit de semnalizare
50 A (at 60 °C) for circuit de alimentare
Irms capacitatea nominala la inchidere: 140 A c.a. for circuit de semnalizare conforming to SR EN 60947-5-1
250 A c.c. for circuit de semnalizare conforming to SR EN 60947-5-1
550 A at 440 V for circuit de alimentare conforming to SR EN 60947
capacitate de rupere nominala: 550 A at 440 V for circuit de alimentare conforming to SR EN 60947
[Icw] curent nominal de scurtcircuit admisibil: 100 A - 1 s for circuit de semnalizare
120 A - 500 ms for circuit de semnalizare
140 A - 100 ms for circuit de semnalizare
60 A 40 °C - 10 min for circuit de alimentare
150 A 40 °C - 1 min for circuit de alimentare
310 A 40 °C - 10 s for circuit de alimentare
430 A 40 °C - 1 s for circuit de alimentare
calibrul fuzibilului asociat: 10 A gG for circuit de semnalizare conforming to SR EN 60947-5-1
63 A gG at <= 690 V coordination tip 1 for circuit de alimentare
63 A gG at <= 690 V coordination tip 2 for circuit de alimentare
impedanta medie: 2 mOhm - Ith 50 A 50 Hz for circuit de alimentare
puterea disipata pe pol: 5 W AC-1
3 W AC-3
3 W AC-3e
[Ui] tensiune nominala de izolatie: Circuit de alimentare 690 V conformitate cu IEC 60947-4-1
Circuit de semnalizare 690 V conformitate cu IEC 60947-1
categorie de supratensiune: III
Grad de poluare: 3
[Uimp] tensiune de tinere la impuls: 6 kV conformitate cu SR EN 60947
nivel de incredere al securitatii: B10d = 1369863 cic contactor cu sarcin? nominal? conformitate cu EN/ISO 13849-1
B10d = 20000000 cic contactor cu sarcin? mecanic? conformitate cu EN/ISO 13849-1
durabilitate mecanica: 15 Mcycles
durabilitate electrica: 1,8 Mcycles 35 A AC-3 la Ue <= 440 V
0,9 Mcycles 50 A AC-1 la Ue <= 440 V
1,8 Mcycles 35 A AC-3e la Ue <= 440 V
tipul circuitului de comanda: C.a./c.c. la 50/60 Hz AC/DC electronic
tehnologie bobine: Limitare de varf bidirectionala incorporata
limite de tensiune circuit de comanda: <= 0.1 Uc (-40…70 °C):eliminare c.a./c.c.
0,85...1,1 Uc (-40…60 °C):opera?ional c.a./c.c.
1...1.1 Uc (60…70 °C):opera?ional c.a./c.c.
consum de energie conectare in VA: 25 VA 50/60 Hz (at 20 °C)
consum de energie conectare in W: 18 W 20 °C)
consum de energie mentinere in VA: 1,6 VA 50/60 Hz (at 20 °C)
consum de energie mentinere in W: 1,1 W la 20 °C
disipare de caldura: 1,1 W at 50/60 Hz
timp de functionare: 45...55 ms inchidere
20...90 ms deschidere
viteza maxima de functionare: 3600 cic/h at 60 °C
conexiuni - borne: Circuit de comanda: borne cu surub 1 1…4 mm^2 - cable stiffness: flexibil fara terminale

de cablu
Circuit de comanda: borne cu surub 2 1…4 mm² - cable stiffness: flexibil fara terminale de cablu
Circuit de comanda: borne cu surub 1 1…4 mm² - cable stiffness: flexibil cu pini
Circuit de comanda: borne cu surub 2 1…2,5 mm² - cable stiffness: flexibil cu pini
Circuit de comanda: borne cu surub 1 1…4 mm² - cable stiffness: solid
Circuit de comanda: borne cu surub 2 1…4 mm² - cable stiffness: solid
Circuit de alimentare: borne cu surub 1 2,5…10 mm² - cable stiffness: flexibil fara terminale de cablu
Circuit de alimentare: borne cu surub 2 2,5…10 mm² - cable stiffness: flexibil fara terminale de cablu
Circuit de alimentare: borne cu surub 1 1…10 mm² - cable stiffness: flexibil cu pini
Circuit de alimentare: borne cu surub 2 1,5…6 mm² - cable stiffness: flexibil cu pini
Circuit de alimentare: borne cu surub 1 1,5…10 mm² - cable stiffness: solid
Circuit de alimentare: borne cu surub 2 2,5…10 mm² - cable stiffness: solid
cuplu de strangere: Circuit de comanda 1,7 N.m - pornit borne cu surub - cu ?urubelni?a plat O 6 mm
Circuit de comanda 1,7 N.m - pornit borne cu surub - cu ?urubelni?a Philips Nr. 2
Circuit de alimentare 2,5 N.m - pornit borne cu surub - cu ?urubelni?a plat O 6 mm
Circuit de alimentare 2,5 N.m - pornit borne cu surub - cu ?urubelni?a Philips Nr. 2
Circuit de alimentare 2,5 N.m - pornit borne cu surub - cu ?urubelni?a pozidriv No 2 M4
Circuit de comanda 1,7 N.m - pornit borne cu surub - cu ?urubelni?a pozidriv No 2 M3.5
compozitie contact auxiliar: 1 NO + 1 NC
tip contacte auxiliare: tip cuplare mecanic? 1 NO + 1 NC conformitate cu SR EN 60947-5-1
tip contact in oglind? 1 NC conformitate cu IEC 60947-4-1
afisare frecventa circuit: 25...400 Hz
tensiunea minima de comutare: 17 V for circuit de semnalizare
curentul minim de comutare: 5 mA for circuit de semnalizare
rezistenta de izolatie: > 10 M? for circuit de semnalizare
timpul de nesuprapunere: 1,5 ms la intreruperea aliment?rii intre contactele NO ?i NC
1,5 ms la energizare intre contactele NO ?i NC
suport de montare: Placa
Sina
standarde: EN/IEC 60947-4-1
SR EN 60947-5-1
UL 60947-4-1
CSA C22.2 No 60947-4-1
IEC 60335-1
certificari produs: CCC
CSA
EAC
UL
KC
DNV-GL
LROS (Lloyds register of shipping)
UKCA
grad de protectie IP: IP20 parte frontala conformitate cu SR EN 60529
incercare climatic?: conformitate cu IACS E10 exposure to damp heat
conformitate cu IEC 60947-1 Annex Q category D exposure to damp heat
temperatura permisa a aerului in jurul aparatului: -40…60 °C
60…70 °C cu declasare
altitudinea de functionare: 0...3000 m
rezistenta la foc: 850 °C conformitate cu IEC 60695-2-1
Intarziere flacara: V1 conformitate cu UL 94
rezistenta mecanica: Vibra?ii contactor deschis (2 Gn, 5...300 Hz)
Vibra?ii contactor inchis (4 Gn, 5...300 Hz)
?ocuri contactor inchis (15 Gn pentru 11 ms)
?ocuri contactor deschis (8 Gn for 11 ms)

inaltime: 85 mm
latime: 45 mm
adancime: 92 mm
greutate neta: 0,442 kg
Pret: 622,69 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/contactor-tesys-d-3p-440-v-38-a-ac-3-100-250-v-c-a-c-c-bobina