



## **SCHNEIDER COMUTATOR ILUMINAT - TASTE 5 FUNCTII CU LUMINA DIN SPATE CU LED-URI MULTICOLOR**

gama de produse: Harmony HMIZ

Tip produs sau componenta: Illuminated USB switch

compatibilitate produs: XBTGC - controller panel

XBTGT2... - advanced touch panel

HMISTO - panou tactil

HMISCU - panou tactil

XBTGT6... - advanced touch panel

HMIGTW - advanced touch panel

XBTGK - graphic display

XBTGT4... - advanced touch panel

XBTGT5... - advanced touch panel

XBTGT7... - advanced touch panel

HMISTU - panou tactil

HMIGTO - advanced touch panel

HMIPSP - S-Panel PC

HMIPSO - S-Panel PC

HMIBMU - Modular Box PC

HMIBMP - Modular Box PC

HMIBMO - Modular Box PC

HMIBMI - Modular Box PC

aplicatie a dispozitivului: Food and beverage

Industrial machines

echipament furnizat: 1 x manual de utilizare

1 x USB type B cable clamp

1 x fixing nut

1 x tightening wrench

1 x anti-rotation tee  
1 x gasket  
1 x insert label  
1 x USB cable type A/B (cu 1 m  
software dedicat: Vijeo Designer >= V6.1 SP2  
tipul conectorului: USB type B  
tip de control: 5 push-buttons cu multi-colour backlit LED  
culoare a capacului: Fata gri inchis  
[Us] tensiune de alimentare nominala: 5 V c.c., tip conector: USB 2.0  
limitele tensiunii de alimentare: 4,75...5,25 V c.c.  
putere consumata in W: 2 W  
rezistenta la socuri: 147 m/s<sup>2</sup> pentru 3 chocks in each direction X, Y and Z conformitate cu IEC 61131-2  
compatibilitate electromagnetica: Test de imunitate la descarcari electrostatice - test level: 9 kV (descarcare in aer) conforming to IEC 61000-4-2  
Test de imunitate la descarcari electrostatice - test level: 6 kV (descarcare pe contact) conforming to IEC 61000-4-2  
Tranzien?i rapizi/test de imunitate la impulsuri de ionizare - test level: 2 kV (prize de putere) conforming to IEC 61000-4-4  
Tranzien?i rapizi/test de imunitate la impulsuri de ionizare - test level: 1 kV (porturi de semnal) conforming to IEC 61000-4-4  
locul de montare: Flat surface  
Cantitate pe set: 1 bucata  
inaltime: 54 mm  
latime: 122 mm  
adancime: 28 mm  
greutate neta: 0,11 kg  
temperatura ambietala pentru depozitare: -20...60 °C  
umiditate relativa: 10...90 % la 0...55 °C fara condensare  
Grad de poluare: 2  
caracteristica de mediu: Corrosive gas free  
altitudinea de functionare: <= 2000 m  
rezistenta la vibratii: 3.5 mm (f= 5...9 Hz) conforming to IEC 61131-2  
grad de protectie IP: IP65 (front panel (in enclosure))  
grad de protectie NEMA: NEMA 4X pentru instalare in interior instalare NEMA 13 pentru enclosed outdoor instalare  
standarde: Standard CSA C22.2 No 142  
UL 60947-1  
Standard CSA C22.2 No 213  
EN 61000-6-4  
ANSI/ISA 12.12.01  
EN 61000-6-2  
Standard EMC 2004/108/EC  
certificari produs: GOST  
UL/cUL  
C-Tick  
UE  
nivel sau clasa: Class I Division 2 Groups A/B/C/D  
Pret: 1.059,96 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/comutator-iluminat-taste-5-functii-cu-lumina-din-spate-cu-led-uri-multicolor>