



### SCHNEIDER MODUL IESIRE ANALOGICA M340 - 8 IESIRI

gama de produse: Modicon X80

Tip produs sau componenta: Modul de iesire analogic

conexiune electrica: 20 cai 1 conector

Isolation between channels: Neizolat

rezolutie de intrare analogica: 16 biti

eroare de masurare:  $\leq 0.25\%$  of full scale  $0...60\text{ }^{\circ}\text{C}$

$0.1\%$  din scala complet?  $25\text{ }^{\circ}\text{C}$

abatere a temperaturii:  $45\text{ ppm}/^{\circ}\text{C}$   $0...20\text{ mA}$

$45\text{ ppm}/^{\circ}\text{C}$   $4...20\text{ mA}$

Minimum crosstalk attenuation: 80 dB

Atenuare zgomot EMI/RFI (de la 100 kHz la 10 MHz): 80 dB

tensiunea de izolatie: 1400 V c.c. between channels and ground

1400 V c.c. between channels and bus

tip detec?ie: Open circuit  $4...20\text{ mA}$

Short circuit  $0...20\text{ mA}$

impedanta ohmica a sarcinii:  $\leq 350\text{ Ohm}$   $0...20\text{ mA}$

$\leq 350\text{ Ohm}$   $4...20\text{ mA}$

nivel de iesire: Nivelinalt

numarul iesirii analogice: 8

tip iesire analogica: Curent  $0...20\text{ mA}$

Curent  $4...20\text{ mA}$

rezolutie de iesire analogica: 16 bi?i

alimentare: Alimentare electrica interna prin rastel

timpe de conversie:  $\leq 4\text{ ms}$

valoarea maxima a conversiei:  $0...21\text{ mA}$   $0...20\text{ mA}$

$0...21\text{ mA}$   $4...20\text{ mA}$

mod revenire: Configurabil

Predefinit

siguranta MTBF: 1500000 H

altitudinea de functionare: 0...2000 m

2000...5000 m cu

stare LED: 1 LED (verde) RUN

1 LED per canal (verde) diagnostic canal

1 LED (rosu) ERR

1 LED (rosu) I/O

greutate neta: 0,15 kg

puterea consumat? in W: 3,6 W 24 V c.c. typical

3,9 W 24 V c.c. maxim

0,35 W 3.3 V c.c. typical

0,48 W 3.3 V c.c. maxim

consum de curent: 150 mA la 3.3 V c.c.

135 mA la 24 V c.c.

rezistenta la vibratii: 3 gn

rezistenta la socuri: 30 gn

temperatura ambietala pentru depozitare: -40...85 °C

temperatura ambientala de functionare: 0...60 °C

umiditate relativa: 5...95 % la 55 °C f?r? condensare

grad de protectie IP: IP20

directive: 2014/35/EU - directiva joasa tensiune

2014/30/EU - directiva de compatibilitate electromagnetica

certificari produs: UE

RCM

CSA

EAC

Certificare navala

UL

standarde: EN/IEC 61010-2-201

EN/IEC 61131-2

UL 61010-2-201

CSA C22.2 No 61010-2-201

Pret: 2.942,54 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modul-iesire-analogica-m340-8-iesiri>