



SCHNEIDER MODUL DE IESIRI ANALOGICE M340 - 2 IESIRI

gama de produse: Modicon X80

Tip produs sau componenta: Modul de iesire analogic

conexiune electrica: 20 cai 1 conector

Isolation between channels: Izolat

eroare de masurare: $\leq 0.2\%$ of full scale $0...60\text{ }^{\circ}\text{C}$

0.1% din scala complet? $25\text{ }^{\circ}\text{C}$

abatere a temperaturii: $30\text{ ppm}/^{\circ}\text{C}$

recalibrare: Calibrat din fabrica

Minimum crosstalk attenuation: 90 dB

Atenuare zgomot EMI/RFI (de la 100 kHz la 10 mHz): 100 dB

tensiunea de izolatie: 1400 V c.c. between channels and ground

1400 V c.c. between channels and bus

750 V c.c. between channels

tip detec?ie: Open circuit $0...20\text{ mA}$

Open circuit $4...20\text{ mA}$

Short circuit $\pm 10\text{ V}$

impedanta ohmica a sarcinii: $\leq 600\text{ Ohm}$ $0...20\text{ mA}$

$\leq 600\text{ Ohm}$ $4...20\text{ mA}$

$\geq 1000\text{ Ohm}$ $\pm 10\text{ V}$

nivel de iesire: Nivelinalt

numarul iesirii analogice: 2

tip iesire analogica: Curent $0...20\text{ mA}$

Curent $4...20\text{ mA}$

Tensiune $\pm 10\text{ V}$

rezolutie de iesire analogica: 16 bi?i + semn

alimentare: Alimentare electrica interna prin rastel

timp de conversie: $\leq 1\text{ ms}$

valoarea maxima a conversiei: +/- 11.25 V +/- 10 V
0...24 mA 0...20 mA
0...24 mA 4...20 mA
mod revenire: Predefinit
Configurabil
siguranta MTBF: 1300000 H
altitudinea de functionare: 0...2000 m
2000...5000 m cu
stare LED: 1 LED (verde) RUN
1 LED per canal (verde) diagnostic canal
1 LED (rosu) ERR
1 LED (rosu) I/O
greutate neta: 0,144 kg
puterea consumat? in W: 2,1 W 24 V c.c. typical
2,8 W 24 V c.c. maxim
0,35 W 3.3 V c.c. typical
0,48 W 3.3 V c.c. maxim
consum de curent: 150 mA la 3.3 V c.c.
110 mA la 24 V c.c.
rezistenta la vibratii: 3 gn
rezistenta la socuri: 30 gn
temperatura ambietala pentru depozitare: -40...85 °C
temperatura ambientala de functionare: 0...60 °C
umiditate relativa: 5...95 % la 55 °C f?r? condensare
grad de protectie IP: IP20
directive: 2014/35/EU - directiva joasa tensiune
2014/30/EU - directiva de compatibilitate electromagnetica
certificari produs: UE
RCM
CSA
EAC
Certificare navala
UL
standarde: EN/IEC 61010-2-201
EN/IEC 61131-2
UL 61010-2-201
CSA C22.2 No 61010-2-201
Pret: 1.546,17 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modul-de-iesiri-analogice-m340-2-iesiri>