



SCHNEIDER CONTACT AUXILIAR - 1 OC SAU 1 SD SAU 1 SDE SAU 1 SDV DE NIVEL SCAZUT

Tip produs sau componenta: Contact auxiliar

nume scurt al dispozitivului: SD

SDV

OF

SDE

aplicatie a dispozitivului: Breaker status monitoring

Compatibilitate gama: Compact (ComPact NS630b...1600)

Compact (ComPact NS1600b...3200)

Compact (Compact INS)

Compact (Compact INV)

Compact (ComPact NSX)

Easypact (EasyPact CVS)

PowerPact (PowerPact Multistandard)

Compact (ComPact NSX DC)

compozitie contacte de semnalizare: 1 NO/NC

Compatibilitate gama: Galaxy PX

Galaxy VL

Galaxy VM

Galaxy VS

Galaxy VX

tip eroare: Defect electric general

semnalizare locala: Indicatie ON/OFF for open/close

Indicator declan?are for indicator declansare releu

Declansare defectiune for electrical fault

tip contacte auxiliare: Nivel scazut

mod de montare: Clipsabil

[I_{th}] curent termic convențional în aer liber: 5 A

Breaking capacity (A): AC-12: 5 A at 24 V c.a. 50/60 Hz

AC-12: 5 A at 48 V c.a. 50/60 Hz

AC-12: 5 A at 110 V c.a. 50/60 Hz

AC-12: 5 A at 220/240 V c.a. 50/60 Hz

AC-12: 5 A at 380/440 V c.a. 50/60 Hz

AC-12: 5 A at 480 V c.a. 50/60 Hz

AC-15: 3 A at 24 V c.a. 50/60 Hz

AC-15: 3 A at 48 V c.a. 50/60 Hz

AC-15: 2,5 A at 110 V c.a. 50/60 Hz

AC-15: 2 A at 220/240 V c.a. 50/60 Hz

AC-15: 1,5 A at 380/440 V c.a. 50/60 Hz

AC-15: 1 A at 480 V c.a. 50/60 Hz

DC-12: 5 A at 24 V c.c.

DC-12: 2,5 A at 48 V c.c.

DC-12: 0,6 A at 110 V c.c.

DC-12: 0,3 A at 250 V c.c.

DC-14: 1 A at 24 V c.c.

DC-14: 0,2 A at 48 V c.c.

DC-14: 0,05 A at 110 V c.c.

DC-14: 0,03 A at 250 V c.c.

sarcina minima: 1 mA la 4 V c.c.

categoria accesorii/piese separate: Piese de schimb pentru Compact NS630b...1600

Piese de schimb pentru Compact NS1600b...3200

Pret: 160,94 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/contact-auxiliar-1-oc-sau-1-sd-sau-1-sde-sau-1-sdv-de-nivel-scazut>