



## **SCHNEIDER CONTACT AUXILIAR DE NIVEL SCAZUT, COMPACT NS630B PANA LA NS3200, FIX, STARE NTRERUPATOR SD, 1 TIP CONTACT COMUTATOR**

Tip produs sau componenta: Contact auxiliar

nume scurt al dispozitivului: SD

aplicatie a dispozitivului: Breaker status monitoring

Compatibilitate gama: Compact (ComPact NS630b...1600)

Compact (ComPact NS1600b...3200)

compozitie contacte de semnalizare: 1 NO/NC

semnalizare locala: Indicator declan?are for indicator declansare releu

tip contacte auxiliare: Nivel scazut

mod de montare: Clipsabil

[I<sub>th</sub>] curent termic conven?ional in aer liber: 5 A

Breaking capacity (A): AC-12: 5 A at 24 V c.a. 50/60 Hz

AC-12: 5 A at 48 V c.a. 50/60 Hz

AC-12: 5 A at 110 V c.a. 50/60 Hz

AC-12: 5 A at 220/240 V c.a. 50/60 Hz

AC-12: 5 A at 380/440 V c.a. 50/60 Hz

AC-12: 5 A at 480 V c.a. 50/60 Hz

AC-15: 3 A at 24 V c.a. 50/60 Hz

AC-15: 3 A at 48 V c.a. 50/60 Hz

AC-15: 2,5 A at 110 V c.a. 50/60 Hz

AC-15: 2 A at 220/240 V c.a. 50/60 Hz

AC-15: 1,5 A at 380/440 V c.a. 50/60 Hz

AC-15: 1 A at 480 V c.a. 50/60 Hz

DC-12: 5 A at 24 V c.c.

DC-12: 2,5 A at 48 V c.c.

DC-12: 0,6 A at 110 V c.c.

DC-12: 0,3 A at 250 V c.c.

DC-14: 1 A at 24 V c.c.

DC-14: 0,2 A at 48 V c.c.

DC-14: 0,05 A at 110 V c.c.

DC-14: 0,03 A at 250 V c.c.

sarcina minima: 1 mA la 4 V c.c.

Pret: 194,21 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contact-auxiliar-de-nivel-scazut-compact-ns630b-pana-la-ns3200-fix-stare-nterupator-sd-1-tip-contact-comutator>