



## **SCHNEIDER CONTACT AUXILIAR - 1 OC CU DESCHIDERE ANTICIPATA - PENTRU NSX400 - 630**

gama de produse: ComPact NSX400...630

ComPact NSX400...630 DC

Gama: ComPact

nume scurt al dispozitivului: contact cu decuplare timpurie

Tip produs sau componenta: Contact auxiliar

aplicatie a dispozitivului: Control

Compatibilitate gama: Compact (ComPact NSX400)

Compact (ComPact NSX630)

Compact Compact NSX400 DC

Compact Compact NSX630 DC

PowerPact (PowerPact L)

tip contacte auxiliare: Standard

operare contacte auxiliare: Decuplare timpurie

mod de montare: Debrosabil

[I<sub>th</sub>] curent termic convențional in aer liber: 6 A

[I<sub>e</sub>] curent nominal de utilizare: AC-12 6 A la 110 V c.a. 50/60 Hz

AC-12 6 A la 220/240 V c.a. 50/60 Hz

AC-12 6 A la 24 V c.a. 50/60 Hz

AC-12 6 A la 380/440 V c.a. 50/60 Hz

AC-12 6 A la 48 V c.a. 50/60 Hz

AC-12 6 A la 480 V c.a. 50/60 Hz

AC-12 6 A la 660/690 V c.a. 50/60 Hz

AC-15 0,1 A la 660/690 V c.a. 50/60 Hz

AC-15 1,5 A la 480 V c.a. 50/60 Hz

AC-15 2 A la 380/440 V c.a. 50/60 Hz

AC-15 4 A la 220/240 V c.a. 50/60 Hz

AC-15 5 A la 110 V c.a. 50/60 Hz

AC-15 6 A la 24 V c.a. 50/60 Hz

AC-15 6 A la 48 V c.a. 50/60 Hz

DC-12 0,3 A la 250 V c.c.

DC-12 0,6 A la 110 V c.c.

DC-12 2,5 A la 48 V c.c.

DC-12 6 A la 24 V c.c.

DC-14 0,03 A la 250 V c.c.

DC-14 0,05 A la 110 V c.c.

DC-14 0,2 A la 48 V c.c.

DC-14 1 A la 24 V c.c.

sarcina minima: 100 mA la 24 V c.c.

Pret: 441,60 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contact-auxiliar-1-oc-cu-deschidere-anticipata-pentru-nsx400-630>