



### SCHNEIDER CONTACT AUXILIAR (ARC) OF/SD - 1 NO/NC

Tip produs sau componenta: Contact auxiliar

nume scurt al dispozitivului: SD

OF

aplicatie a dispozitivului: Breaker status monitoring

Compatibilitate gama: PowerPact (PowerPact B)

Compact (ComPact NSXm)

compozitie contacte de semnalizare: 1 NO/NC

tip eroare: Suprasarcina

Scurtcircuit

semnalizare locala: Indicatie ON/OFF for open/close

Indicator declan?are for indicator declansare releu

tip contacte auxiliare: Standard

mod de montare: Clipsabil

[I<sub>th</sub>] curent termic conven?ional in aer liber: 5 A

Breaking capacity (A): AC-12: 5 A at 24 V c.a. 50/60 Hz

AC-12: 5 A at 48 V c.a. 50/60 Hz

AC-12: 5 A at 110...127 V c.a. 50/60 Hz

AC-12: 5 A at 220/240 V c.a. 50/60 Hz

AC-12: 5 A at 380/440 V c.a. 50/60 Hz

AC-12: 5 A at 660/690 V c.a. 50/60 Hz

AC-15: 5 A at 24 V c.a. 50/60 Hz

AC-15: 5 A at 48 V c.a. 50/60 Hz

AC-15: 4 A at 110...127 V c.a. 50/60 Hz

AC-15: 3 A at 220/240 V c.a. 50/60 Hz

AC-15: 2,5 A at 380/440 V c.a. 50/60 Hz

AC-15: 0,1 A at 660/690 V c.a. 50/60 Hz

DC-12: 5 A at 24 V c.c. 50/60 Hz

DC-12: 2,5 A at 48 V c.c. 50/60 Hz

DC-12: 0,6 A at 110 V c.c. 50/60 Hz

DC-12: 0,3 A at 250 V c.c.

DC-13: 2,5 A at 24 V c.c.

DC-13: 1,2 A at 48 V c.c.

DC-13: 0,35 A at 110 V c.c.

DC-13: 0,05 A at 250 V c.c.

DC-14: 1 A at 24 V c.c.

DC-14: 0,2 A at 48 V c.c.

DC-14: 0,05 A at 110 V c.c.

DC-14: 0,03 A at 250 V c.c.

sarcina minima: 2 mA la 17 V c.c.

terminal auxiliar de conectare: arc

lungimea de dezizolare a cablului: 8 mm for fata connection

Pret: 98,76 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/contact-auxiliar-arc-of-sd-1-no-nc>