



SCHNEIDER CONTACT AUXILIAR - 2 OC CU DECUPLARE RAPIDA - NS630B - 1600 - FIX

Tip produs sau componenta: Contact auxiliar
Compatibilitate gama: Compact (ComPact NS630b...1600)
compozitie contacte de semnalizare: 1 NO/NC
tip contacte auxiliare: Standard
operare contacte auxiliare: Decuplare timpurie
mod de montare: Clipsabil
[I_{th}] curent termic conventional in aer liber: 6 A
Breaking capacity (A): AC-12: 6 A at 24 V c.a. 50/60 Hz
AC-12: 6 A at 48 V c.a. 50/60 Hz
AC-12: 6 A at 110 V c.a. 50/60 Hz
AC-12: 6 A at 220/240 V c.a. 50/60 Hz
AC-12: 6 A at 380/440 V c.a. 50/60 Hz
AC-12: 6 A at 480 V c.a. 50/60 Hz
AC-12: 6 A at 660/690 V c.a. 50/60 Hz
AC-15: 6 A at 24 V c.a. 50/60 Hz
AC-15: 6 A at 48 V c.a. 50/60 Hz
AC-15: 5 A at 110 V c.a. 50/60 Hz
AC-15: 4 A at 220/240 V c.a. 50/60 Hz
AC-15: 2 A at 380/440 V c.a. 50/60 Hz
AC-15: 1,5 A at 480 V c.a. 50/60 Hz
AC-15: 0,1 A at 660/690 V c.a. 50/60 Hz
DC-12: 6 A at 24 V c.c.
DC-12: 2,5 A at 48 V c.c.
DC-12: 0,6 A at 110 V c.c.
DC-12: 0,3 A at 250 V c.c.
DC-14: 1 A at 24 V c.c.

DC-14: 0,2 A at 48 V c.c.

DC-14: 0,05 A at 110 V c.c.

DC-14: 0,03 A at 250 V c.c.

sarcina minima: 100 mA la 24 V c.c.

Pret: 322,01 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contact-auxiliar-2-oc-cu-decuplare-rapida-ns630b-1600-fix>