



## **SCHNEIDER 2 CONTACTE AUXILIARE DE POZITIE CE/CD CONECTAT/DECONNECTAT - OC - PT. NS100 - 250**

nume scurt al dispozitivului: CE

CD

Tip produs sau componenta: Carriage switch

aplicatie a dispozitivului: Monitorizare

Compatibilitate gama: Compact (ComPact NSX100)

Compact (ComPact NSX160)

Compact (ComPact NSX250)

Compact (ComPact NSX400)

Compact (ComPact NSX630)

compozitie contacte de semnalizare: 2 NO/NC

tip contacte auxiliare: Standard

operare contacte auxiliare: CE/CD

mod de montare: Debrosabil

[I<sub>th</sub>] curent termic conven?ional in aer liber: 6 A

[I<sub>e</sub>] curent nominal de utilizare: AC-12 6 A la 110 V c.a. 50/60 Hz

AC-12 6 A la 220/240 V c.a. 50/60 Hz

AC-12 6 A la 24 V c.a. 50/60 Hz

AC-12 6 A la 380/440 V c.a. 50/60 Hz

AC-12 6 A la 48 V c.a. 50/60 Hz

AC-12 6 A la 480 V c.a. 50/60 Hz

AC-12 6 A la 660/690 V c.a. 50/60 Hz

AC-15 0,1 A la 660/690 V c.a. 50/60 Hz

AC-15 1,5 A la 480 V c.a. 50/60 Hz

AC-15 2 A la 380/440 V c.a. 50/60 Hz

AC-15 4 A la 220/240 V c.a. 50/60 Hz

AC-15 5 A la 110 V c.a. 50/60 Hz

AC-15 6 A la 24 V c.a. 50/60 Hz

AC-15 6 A la 48 V c.a. 50/60 Hz

DC-12 0,3 A la 250 V c.c.

DC-12 0,6 A la 110 V c.c.

DC-12 2,5 A la 48 V c.c.

DC-12 6 A la 24 V c.c.

DC-14 0,03 A la 250 V c.c.

DC-14 0,05 A la 110 V c.c.

DC-14 0,2 A la 48 V c.c.

DC-14 1 A la 24 V c.c.

sarcina minima: 100 mA la 24 V c.c.

Cantitate pe set: 2

Pret: 250,64 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-contacte-auxiliare-de-pozitie-ce-cd-conectat-deconectat-oc-pt-ns100-250>