



## SCHNEIDER ACTUATOR UNIVERSAL DE REGLARE KNX LL 4X230V/250W

Gama: KNX

Tip produs sau componenta: Element de dimare

mod de operare: Manual

Sistem magistrala KNX

tip magistrala: KNX

total number of 18 mm modules: 8

suport de montare: Sina DIN

[Ue] tensiune nominala: 220...230 V

110...130 V

frecventa retea electrica: 50/60 Hz

numar de iesiri: 4

semnalizare locala: LED

tip de sarcina: Lampi cu incandescenta:4...250 W la 230 V 50 Hz c.a.

Lampii cu halogen:4...250 W la 230 V c.a.

Lampii cu halogeni de joasa tensiune:25...250 VA la 12 V c.a. (transformator toroidal)

Lampii cu halogeni de joasa tensiune:4...250 W la 12 V c.a. (transformator electronic)

Lampa fluorescenta compacta:4...125 W la 230 V c.a. (mod RC)

Lampa cu consum redus de energie:4...125 W la 230 V c.a. (mod RC)

Lampa LED:4...125 W la 230 V c.a. (mod RC)

Lampa fluorescenta compacta:25...45 W la 230 V c.a. (mod RL LED)

Lampa cu consum redus de energie:25...45 W la 230 V c.a. (mod RL LED)

Lampa LED:25...45 W la 230 V c.a. (mod RL LED)

Lampii cu incandescenta:4...125 W la 110 V c.a.

Lampii cu halogen:4...125 W la 110 V c.a.

Lampii cu halogeni de joasa tensiune:25...125 VA la 12 V c.a. (transformator toroidal)

Lampii cu halogeni de joasa tensiune:4...125 W la 12 V c.a. (transformator electronic)

Lampa fluorescenta compacta:4...60 W la 110 V c.a. (mod RC)

Lampa cu consum redus de energie:4...60 W la 110 V c.a. (mod RC)

Lampa LED:4...60 W la 110 V c.a. (mod RC)

Lampa fluorescenta compacta:12...22 W la 110 V c.a. (mod RL LED)

Lampa cu consum redus de energie:12...22 W la 110 V c.a. (mod RL LED)

Lampa LED:12...22 W la 110 V c.a. (mod RL LED)

culoare: Alb

grad de protectie IP: IP20

Pret: 2.369,21 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/actuator-universal-de-reglare-knx-ii-4x230v-250w>