



SCHNEIDER MODUL MATRE AS-I V3

gama de produse: Modicon X80

Tip produs sau componenta: Master module

profil AS-Interface: M4 master profile

S7.3 slave profile

S7.A.7 slave profile

S7.A.A slave profile

S7.A.8 slave profile

S7.A.9 slave profile

S6.0.X slave profile

adresare: Standard si extins

timp de ciclu: 5 ms pentru 31

10 ms pentru 62

conexiune electrica: 1 conector tat? SUB-D, 3 pini

sumar de slave: 124 server device(s) for discrete inputs and outputs - standard

124 server device(s) for analog inputs and outputs - standard

496 server device(s) for discrete inputs and outputs - extins

124 server device(s) for analog inputs and outputs - extins

distanța maxima cablu intre dispozitive: 100 m

200 m line extension

300 m 2 repeaters

500 m 2 repeaters and the master at the middle

semnalizare locala: 1 LED (verde) for module active (RUN)

1 LED (rosu) for eroare modul (ERR)

1 LED (verde) for displays the group of 31 slaves (A/B)

1 LED (rosu) for defect modul I/O (I/O)

32 LEDs for diagnostics of the AS-Interface and each slave

1 LED (verde) for ASI power

1 LED (rosu) for defect
consum de curent: 160 mA la 3.3 V c.c.
format de modul: Standard
greutate neta: 0,34 kg
directive: 2014/35/EU - directiva joasa tensiune
2014/30/EU - directiva de compatibilitate electromagnetica
2014/34/EU - ATEX directive
certificari produs: UE
UL
CSA
RCM
EAC
Certificare navala
ATEX zona 2/22
IECEX zone 2/22
standarde: EN/IEC 61131-2
EN/IEC 61010-2-201
UL 61010-2-201
CSA C22.2 No 61010-2-201
IACS E10
EN/IEC 61000-6-5, interface type 1 and type 2
EN/IEC 61850-3, location G
Standard EN/IEC 60079-0
caracteristica de mediu: Hazardous location
caracteristica de mediu: Hazardous location class I division 2
temperatura ambientala de functionare: 0...60 °C
temperatura ambietala pentru depozitare: -40...70 °C
grad de protectie IP: IP20
Pret: 2.015,22 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modul-matre-as-i-v3>