

SCHNEIDER VERSIUNEA VOPSITA A BMEH582040, PT MEDII POLUATE

gama de produse: Modicon M580
Tip produs sau componenta: Redundant processor module
material de impregnare: Acoperit conform
numar de rackuri: 1
intrare/iesire specifica aplicatiei: Legatura seriala
HART
Contor
Control miscare
Marcare temporala precisa
Encoder SSI
verificari: Control de proces
canale de control: Bucle programabile
tip de conexiune integrata: 1 Ethernet TCP/IP pentru service port
2 Ethernet TCP/IP pentru device network
USB type mini B
1 Ethernet pentru HSBY port
numar de statii I/O la distanta: 8 - 2 pe X80 remote drop
numar echipamente distribuite: 64
procesorul modulului de comunicatie: 2 Modul de comunicatie Ethernet
16 Modul interfata AS
serviciu de comunicare: RIO scanner
Scanner DIO
descriere memorie: Extensibil flash, 4 GB pentru stocare date
Integrat RAM, 10 kB pentru Memorie
Integrat RAM, 8 MB pentru program
Integrat RAM, 768 kB pentru date
structura aplicatie: 1 operatie rapida periodica

1 operatie principala ciclica/periodica
numar de instructiuni pe ms: 30 Kinst/ms 65 % Boolean + 35 % aritmetica fix?
40 Kinst/ms 100 % Boolean
consum de curent: 270 mA la 24 V c.c.
siguranta MTBF: 650000 H
marcaj: CE
rezistenta la vibratii: 3 gn
rezistenta la socuri: 30 gn
temperatura ambientala de functionare: -25…60 °C
temperatura ambietala pentru depozitare: -40…85 °C
altitudinea de functionare: 0...2000 m
2000...5000 m cu
umiditate relativa: 5…95 % la 55 °C f?r? condensare
grad de protectie IP: IP20
directive: 2014/35/EU - directiva joasa tensiune
2014/30/EU - directiva de compatibilitate electromagnetica
2014/34/EU - ATEX directive
certificari produs: UE
UL
CSA
RCM
EAC
Certificare navala
ATEX zona 2/22
IECEx zone 2/22
standarde: IEC 61131-2
IEC 61010-2-201
UL 61010-2-201
CSA C22.2 No 61010-2-201
IACS E10
EN/IEC 61000-6-5, interface type 1 and type 2
EN/IEC 61850-3, location G
IEC 60079-0
caracteristica de mediu: Gas resistant class Gx conformitate cu ISA S71.04
Gas resistant class 3C4 conformitate cu IEC 60721-3-3
Dust resistant class 3S4 conformitate cu IEC 60721-3-3
Sand resistant class 3S4 conformitate cu IEC 60721-3-3
Salt resistant nivel 2 conformitate cu IEC 68252
Mold growth resistant class 3B2 conformitate cu IEC 60721-3-3
Fungal spore resistant class 3B2 conformitate cu IEC 60721-3-3
Hazardous location class I division 2
tratament protector: Conformal coating
alimentare: Alimentare electrica interna prin rastel
stare LED: 1 LED (verde) func?ionare procesor (RUN)
1 LED (rosu) defect procesor sau sistem(ERR)
1 LED (rosu) defect modul I/O (I/O)
1 LED (verde) Descarcare in curs ()
1 LED (rosu) Card memorie sau eroare flash CPU (rezerva)
1 LED (green/red) ETH MS (Status configurare port Ethernet)
1 LED (green/red) Eth NS (Status retea Ethernet)
1 LED (verde) peer processor running (REMOTE RUN)
1 LED (verde) processor ID set to A (A)
1 LED (verde) processor ID set to B (B)
1 LED (verde) processor acting as Primary (PRIM)

1 LED (verde) processor acting as Standby (STBY)
1 LED (verde) I/O values overrided by user (FORCED IO)
1 LED (verde) Hot standby link status (Hsby Diag)
greutate neta: 0,849 kg
Pret: 25.421,25 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/versiunea-vopsita-a-bmeh582040-pt-medii-poluate