



### SCHNEIDER MOTOR BOBINA - 48 A - PT. VARIATOR DE VITEZA

Tip produs sau componenta: Starter de motor

Compatibilitate gama: Altivar 71

Altivar 61

aplicatie specifica produsului: Filtru de iesire

[In] curent nominal: 48 A

compatibilitate produs: ATV61H075N4

ATV61HU15N4

ATV61HU22N4

ATV61HU30N4

ATV61HU40N4

ATV61W075N4

ATV61W075N4C

ATV61WU15N4

ATV61WU15N4C

ATV61WU22N4

ATV61WU22N4C

ATV61WU30N4

ATV61WU30N4C

ATV61WU40N4

ATV61WU40N4C

ATV71H075N4

ATV71HU15N4

ATV71HU22N4

ATV71HU30N4

ATV71HU40N4

ATV71P075N4Z

ATV71PU15N4Z

ATV71PU22N4Z  
ATV71PU30N4Z  
ATV71PU40N4Z  
ATV71W075N4  
ATV71WU15N4  
ATV71WU22N4  
ATV71WU30N4  
ATV71WU40N4  
ATV61HD11N4  
ATV61HD11Y  
ATV61HD15N4  
ATV61HD18N4  
ATV61HU22S6X  
ATV61HU30M3  
ATV61HU30S6X  
ATV61HU30Y  
ATV61HU40M3  
ATV61HU40S6X  
ATV61HU40Y  
ATV61HU55M3  
ATV61HU55N4  
ATV61HU55S6X  
ATV61HU55Y  
ATV61HU75M3  
ATV61HU75N4  
ATV61HU75S6X  
ATV61HU75Y  
ATV61WD11N4  
ATV61WD11N4C  
ATV61WD15N4  
ATV61WD15N4C  
ATV61WD18N4  
ATV61WD18N4C  
ATV61WU55N4  
ATV61WU55N4C  
ATV61WU75N4  
ATV61WU75N4C  
ATV71HD11N4  
ATV71HD11Y  
ATV71HD15N4  
ATV71HD18N4  
ATV71HU15S6X  
ATV71HU22S6X  
ATV71HU22Y  
ATV71HU30M3  
ATV71HU30S6X  
ATV71HU30Y  
ATV71HU40M3  
ATV71HU40S6X  
ATV71HU40Y  
ATV71HU55M3  
ATV71HU55N4  
ATV71HU55S6X  
ATV71HU55Y

ATV71HU75M3  
ATV71HU75N4  
ATV71HU75S6X  
ATV71HU75Y  
ATV71PD11N4Z  
ATV71PU55N4Z  
ATV71PU75N4Z  
ATV71WD11N4  
ATV71WD15N4  
ATV71WD18N4  
ATV71WU55N4  
ATV71WU75N4

cantitate Incorporata: 1

conexiune electrica: Borna, capacitate conexiune: 10 mm<sup>2</sup> / AWG 6

lungimea maxima a cablului motorului: 200 m cablu ecranat P motor 2,2...7,5 kW la 200...240 V 1

260 m cablu neecranat P motor 2,2...7,5 kW la 200...240 V 1

85 m cablu ecranat P motor 0,75...18,5 kW la 380...480 V 1

95 m cablu neecranat P motor 0,75...18,5 kW la 380...480 V 1

50 m cablu ecranat P motor 2,2...7,5 kW la 500...600 V 1

100 m cablu neecranat P motor 2,2...7,5 kW la 500...600 V 1

45 m cablu ecranat P motor 2,2...11 kW la 500...690 V 1

70 m cablu neecranat P motor 2,2...11 kW la 500...690 V 1

dv/dt: 500 V/μs maxim la 400 V

750 V/μs maxim la 500 V

1000 V/μs maxim la 690 V

pierderi termice: 250 W

cuplu de strangere: 1,5 N.m

maximum drive output frequency: 100 Hz

tip de protectie: Protectie termica de termostat programabil, temperatura de declansare: 125 °C pentru

temperatura ambientala de utilizare: -10...50 °C

greutate neta: 8 kg

grad de protectie IP: IP20 (cu kituri VW3A9612,613)

IPO0

temperatura ambietala pentru depozitare: -25...70 °C

Pret: 1.257,84 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/motor-bobina-48-a-pt-variator-de-viteza>