



### SCHNEIDER CANALIS KT 4X4000AL COUDE A PLAT N2

Gama: Canalis

nume produs: KT

Tip produs sau componenta: Elbow

descriere bara colectoare: Standard

nume scurt al dispozitivului: KTA

aplicatie a dispozitivului: Change direction

material: Aluminiu

[Ie] curent nominal de utilizare: 4000 A la 35 °C

polarity: 3L + N + PE

tip modificare directie: 1 plat right

unghi de functionare: 90 °

earth conductor: Standard earth

short-circuit level: Standard version

echipament furnizat: Jointing unit

Trunking unit

material carcasa: Polyester film

Material contacte: Copper

[Ue] tensiune nominala: 1000 V

frecventa retea electrica: 50/60 Hz

[Ui] tensiunea nominala de izolatie: 1000 V

[Icw] curent nominal admisibil de scurta durata: 90 kA

[Ipk] curent nominal de tinere la varf: 198 kA

camp magnetic radiat: 3  $\mu$ T

limita de stres termic: 8100000 kA<sup>2</sup>.s

THDI: 0...15 % 4000 A

cadere de tensiune maxima: pozitie neutrului: Stanga

standarde: IEC 61439-6

IEC 61439-1

Tip dimensiune: Made to measure

latime: 140 mm

inaltime: 404 mm

lungime: 1 301...600 mm

2 301...1400 mm

culoare: Alb (RAL 9001)

sarcina liniara: 45 kg/m

grad de protectie IP: IP55 conforming to SR EN 60529

grad de protectie IK: IK08 conforming to IEC 62262

derating factor: 0...35 °C (100 % of In)

35...40 °C (97 % of In)

40...45 °C (93 % of In)

45...50 °C (90 % of In)

50...55 °C (86 % of In)

Pret: 28.735,74 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/canalis-kt-4x4000al-coude-a-plat-n2>