



SCHNEIDER FILTRU SINUSOIDAL IESIRE, 15 A, PT UNITATE DE VITEZA VARIABILA

Tip produs sau componenta: Filtru sinusoidal

Compatibilitate gama: Altivar Process ATV900

Altivar Process ATV600

aplicatie specifica produsului: Filtru de iesire

lungimea maxima a cablului motorului: 1000 m cablu neecranat

500 m cablu ecranat

[In] curent nominal: 15 A

pierderi termice: 76 W la 4 kHz

compatibilitate produs: Variable speed drive ATV630 wall mount, 3 kW, 380...480 V

Variable speed drive ATV630 wall mount, 4 kW, 380...480 V

Variable speed drive ATV630 wall mount, 5,5 kW, 380...480 V

Variable speed drive ATV630 wall mount, 1,5 kW, 200...240 V

Variable speed drive ATV630 wall mount, 2,2 kW, 200...240 V

Variable speed drive ATV630 wall mount, 3 kW, 200...240 V

Variable speed drive ATV650 wall mount, 3 kW, 380...480 V

Variable speed drive ATV650 wall mount, 4 kW, 380...480 V

Variable speed drive ATV650 wall mount, 5,5 kW, 380...480 V

Variable speed drive ATV930 wall mount, 3 kW, 380...480 V

Variable speed drive ATV930 wall mount, 4 kW, 380...480 V

Variable speed drive ATV930 wall mount, 5,5 kW, 380...480 V

Variable speed drive ATV930 wall mount, 1,5 kW, 200...240 V

Variable speed drive ATV930 wall mount, 2,2 kW, 200...240 V

Variable speed drive ATV930 wall mount, 3 kW, 200...240 V

Variable speed drive ATV950 wall mount, 3 kW, 380...480 V

Variable speed drive ATV950 wall mount, 4 kW, 380...480 V

Variable speed drive ATV950 wall mount, 5,5 kW, 380...480 V

conexiune electrica: bloc de conexiuni, capacitate conexiune: 6 mm² / AWG 10
altitudinea de functionare: ≤ 1000 m f?r? declasarea curentului
1000...4000 m cu declasarea curentului cu 1 % pe 100 m
frecventa de comutare: 4...8 kHz
frecventa maxima de iesire: 100 Hz
cadere de tensiune maxima la incarcare nominala: 8 %
tensiunea admisa: 480 V c.a.
curent maxim: 1.20 x nominal current (durata = 60 s)
latime: 220 mm
inaltime: 455 mm
adancime: 210 mm
greutate neta: 13,5 kg
grad de protectie IP: IP20
IP21 (with kit VW3A53901)
caracteristica de mediu: Biological pollution resistance class 3B1 conformitate cu IEC 60721-3-3
Chemical pollution resistance class 3C3 conformitate cu IEC 60721-3-3
Dust pollution resistance class 3S3 conformitate cu IEC 60721-3-3
grad de poluare: 2 conformitate cu IEC 61800-5-1
umiditate relativa: 5...95 % f?r? condensare
temperatura ambientala de utilizare: 50...60 °C (cu diminuarea curentului cu 1.5% par °C)
-15...50 °C (f?r? declasarea curentului)
temperatura ambietala pentru depozitare: -40...70 °C
rezistenta mecanica: ?ocuri class 3M4 conformitate cu IEC 60721-3-3
Vibra?ii class 3M4 conformitate cu IEC 60721-3-3
Pret: 2.779,21 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/filtru-sinusoidal-iesire-15-a-pt-unitate-de-viteza-variabila>