



SCHNEIDER MOTOR BOBINA - 90 A - PT. VARIATOR DE VITEZA

Tip produs sau componenta: Starter de motor

Compatibilitate gama: Altivar 212

Altivar 61

Altivar 71

Altivar Process ATV900

Altivar Process ATV600

aplicatie specifica produsului: Filtru de iesire

[In] curent nominal: 90 A

compatibilitate produs: ATV61H075N4

ATV61HU15N4

ATV61HU22N4

ATV61HU30N4

ATV61HU40N4

ATV61W075N4

ATV61W075N4C

ATV61WU15N4

ATV61WU15N4C

ATV61WU22N4

ATV61WU22N4C

ATV61WU30N4

ATV61WU30N4C

ATV61WU40N4

ATV61WU40N4C

ATV71H075N4

ATV71HU15N4

ATV71HU22N4

ATV71HU30N4

ATV71HU40N4
ATV71P075N4Z
ATV71PU15N4Z
ATV71PU22N4Z
ATV71PU30N4Z
ATV71PU40N4Z
ATV71W075N4
ATV71WU15N4
ATV71WU22N4
ATV71WU30N4
ATV71WU40N4
ATV61HD11N4
ATV61HD11Y
ATV61HD15N4
ATV61HD18N4
ATV61HU22S6X
ATV61HU30M3
ATV61HU30S6X
ATV61HU30Y
ATV61HU40M3
ATV61HU40S6X
ATV61HU40Y
ATV61HU55M3
ATV61HU55N4
ATV61HU55S6X
ATV61HU55Y
ATV61HU75M3
ATV61HU75N4
ATV61HU75S6X
ATV61HU75Y
ATV61WD11N4
ATV61WD11N4C
ATV61WD15N4
ATV61WD15N4C
ATV61WD18N4
ATV61WD18N4C
ATV61WU55N4
ATV61WU55N4C
ATV61WU75N4
ATV61WU75N4C
ATV71HD11N4
ATV71HD11Y
ATV71HD15N4
ATV71HD18N4
ATV71HU15S6X
ATV71HU22S6X
ATV71HU22Y
ATV71HU30M3
ATV71HU30S6X
ATV71HU30Y
ATV71HU40M3
ATV71HU40S6X
ATV71HU40Y
ATV71HU55M3

ATV71HU55N4
ATV71HU55S6X
ATV71HU55Y
ATV71HU75M3
ATV71HU75N4
ATV71HU75S6X
ATV71HU75Y
ATV71PD11N4Z
ATV71PU55N4Z
ATV71PU75N4Z
ATV71WD11N4
ATV71WD15N4
ATV71WD18N4
ATV71WU55N4
ATV71WU75N4
ATV212H075M3X
ATV212H075N4
ATV212HD11M3X
ATV212HD11N4
ATV212HU15M3X
ATV212HU15N4
ATV212HU22M3X
ATV212HU22N4
ATV212HU30M3X
ATV212HU30N4
ATV212HU40M3X
ATV212HU40N4
ATV212HU55M3X
ATV212HU55N4
ATV212HU75M3X
ATV212HU75N4
ATV212W075N4
ATV212W075N4C
ATV212WD11N4
ATV212WD11N4C
ATV212WU15N4
ATV212WU15N4C
ATV212WU22N4
ATV212WU22N4C
ATV212WU30N4
ATV212WU30N4C
ATV212WU40N4
ATV212WU40N4C
ATV212WU55N4
ATV212WU55N4C
ATV212WU75N4
ATV212WU75N4C
ATV61HD11M3X
ATV61HD15M3X
ATV61HD15Y
ATV61HD18M3X
ATV61HD18Y
ATV61HD22M3X
ATV61HD22N4

ATV61HD22Y
ATV61HD30N4
ATV61HD30Y
ATV61HD37N4
ATV61WD22N4
ATV61WD22N4C
ATV61WD30N4
ATV61WD30N4C
ATV61WD37N4
ATV61WD37N4C
ATV71HD11M3X
ATV71HD15M3X
ATV71HD15Y
ATV71HD18M3X
ATV71HD18Y
ATV71HD22M3X
ATV71HD22N4
ATV71HD22Y
ATV71HD30Y
ATV71HD37N4
ATV71WD30N4
ATV71WD37N4

ATV630 variable speed drive - 2,2 kW, 500...690 V trifazic

ATV630 variable speed drive - 3 kW, 500...690 V trifazic

ATV630 variable speed drive - 4 kW, 500...690 V trifazic

ATV630 variable speed drive - 5,5 kW, 500...690 V trifazic

ATV630 variable speed drive - 7,5 kW, 500...690 V trifazic

ATV630 variable speed drive - 11 kW, 500...690 V trifazic

ATV930 variable speed drive - 2,2 kW, 500...690 V trifazic

ATV930 variable speed drive - 3 kW, 500...690 V trifazic

ATV930 variable speed drive - 4 kW, 500...690 V trifazic

ATV930 variable speed drive - 5,5 kW, 500...690 V trifazic

ATV930 variable speed drive - 7,5 kW, 500...690 V trifazic

ATV930 variable speed drive - 11 kW, 500...690 V trifazic

ATV630 variable speed drive, 3 CP, 600 V trifazic

ATV630 variable speed drive, 5 CP, 600 V trifazic

ATV630 variable speed drive, 7,5 CP, 600 V trifazic

ATV630 variable speed drive, 10 CP, 600 V trifazic

ATV630 variable speed drive, 15 CP, 600 V trifazic

ATV930 variable speed drive, 3 CP, 600 V trifazic

ATV930 variable speed drive, 5 CP, 600 V trifazic

ATV930 variable speed drive, 7,5 CP, 600 V trifazic

ATV930 variable speed drive, 10 CP, 600 V trifazic

ATV930 variable speed drive, 15 CP, 600 V trifazic

cantitate Incorporata: 1

conexiune electrica: Bare sub?iri diametru: 9 mm

lungimea maxima a cablului motorului: 300 m cablu ecranat P motor 2,2...7,5 kW la 200...240 V 1

300 m cablu neecranat P motor 2,2...7,5 kW la 200...240 V 1

150 m cablu ecranat P motor 11...22 kW la 200...240 V 1

300 m cablu neecranat P motor 11...22 kW la 200...240 V 1

160 m cablu ecranat P motor 0,75...18,5 kW la 380...480 V 1

200 m cablu neecranat P motor 0,75...18,5 kW la 380...480 V 1

140 m cablu ecranat P motor 22...30 kW la 380...480 V 1

170 m cablu neecranat P motor 22...30 kW la 380...480 V 1

75 m cablu ecranat P motor 2,2...7,5 kW la 500...600 V 1

150 m cablu neecranat P motor 2,2...7,5 kW la 500...600 V 1

65 m cablu ecranat P motor 2,2...30 kW la 500...690 V 1

100 m cablu neecranat P motor 2,2...30 kW la 500...690 V 1

150 m cablu ecranat P motor 2,2...7,5 kW la 500...690 V 2

250 m cablu neecranat P motor 2,2...7,5 kW la 500...690 V 2

100 m cablu ecranat P motor 2,2...30 kW la 500...690 V 2

150 m cablu neecranat P motor 2,2...30 kW la 500...690 V 2

97 m cablu ecranat P motor 37 kW la 380...480 V 1

166 m cablu neecranat P motor 37 kW la 380...480 V 1

dv/dt: 500 V/ μ s maxim la 400 V

750 V/ μ s maxim la 500 V

1000 V/ μ s maxim la 690 V

pierderi termice: 350 W

maximum drive output frequency: 100 Hz

tip de protectie: Protectie termica de termostat programabil, temperatura de declansare: 125 °C pentru

temperatura ambientala de utilizare: -10...50 °C

greutate neta: 10 kg

grad de protectie IP: IP20 (cu kituri VW3A9612,613)

IP00

temperatura ambietala pentru depozitare: -25...70 °C

Pret: 2.141,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/motor-bobina-90-a-pt-variator-de-viteza>