



## SCHNEIDER SPACELOGIC, AUTOMAT AS-P (HW)

Tip produs sau componenta: Controler  
certificari produs: BTL

UE

cULus

FCC partea 15 clasa B

ICES-003

serviciu de comunicare: SNMP network management

Notificare prin e-mail SMTP

SMTPS e-mail notification

Modbus TCP client

Modbus TCP server

consum de curent: 400 mA

nume scurt al dispozitivului: AS-P

Rezistenta la foc: UL94V0-5VB

grad de protectie IP: IP20

adancime: 64 mm

inaltime: 114 mm

greutate neta: 321 g

latime: 90 mm

temperatura ambientala de functionare: 0...50 °C

temperatura ambietala pentru depozitare: -20...70 °C

tip memorie: 512 MB RAM

4 GB flash

Standarde: UL 94

UL 916

FCC CFR 47 part 15

Gama: EcoStruxure Building Operation

marca de produs: Schneider Electric  
capacitate procesor I/O limitator: 464 I/O, 29 modules  
material: ABS/PC  
montare produs: On base  
Sina DIN  
servicii Web: TLS 1.0  
HTTP server  
Programmable scripts : alarm summaries, report management  
tip de conexiune integrata: USB 2.0 tip A  
USB type mini B  
nume procesor: Spear 320s  
Compatibilitate gama: EcoStruxure Building Operation TB-ASP-W1 terminal base  
EcoStruxure Building Operation TB-AS-W1 terminal base  
protocol port de comunicare: BACnet  
Modbus TCP master RS485  
Modbus TCP slave RS485  
HTTPS RJ45  
HTTP RJ45  
LON TP/FT-10  
umiditate relativa: 0...95 %  
Pret: 18.499,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/spacelogic-automat-as-p-hw>