



SCHNEIDER SPACELOGIC, AUTOMAT AS-P SMK (HW)

Tip produs sau componenta: Controler

certificari produs: cULus

UE

ICES-003

FCC partea 15 clasa B

BTL

serviciu de comunicare: SNMP network management

Notificare prin e-mail SMTP

SMTPS e-mail notification

Modbus TCP client

Modbus TCP server

consum de curent: 400 mA

nume scurt al dispozitivului: AS-P-SMK

Rezistenta la foc: UL94V0-5VB

grad de protectie IP: IP20

adancime: 64 mm

inaltime: 114 mm

greutate neta: 321 g

latime: 90 mm

temperatura ambientala de functionare: 0...50 °C

temperatura ambietala pentru depozitare: -20...70 °C

tip memorie: 512 MB RAM

4 GB flash

Standarde: FCC CFR 47 part 15

UL 94

UL 916

UL 864

Gama: EcoStruxure Building Operation
marca de produs: Schneider Electric
capacitate procesor I/O limitator: 464 I/O, 29 modules
material: ABS/PC
montare produs: On base
Sina DIN
servicii Web: HTTP server
Programmable scripts : alarm summaries, report management
TLS 1.0
tip de conexiune integrata: USB 2.0 tip A
USB type mini B
nume procesor: Spear 320s
Compatibilitate gama: EcoStruxure Building Operation TB-ASP-W1 terminal base
EcoStruxure Building Operation TB-AS-W1 terminal base
protocol port de comunicare: BACnet
Modbus TCP master RS485
Modbus TCP slave RS485
HTTPS RJ45
HTTP RJ45
LON TP/FT-10
umiditate relativa: 0...95 %
Pret: 37.288,41 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/spacelogic-automat-as-p-smk-hw>