



## SCHNEIDER SPACELOGIC, AUTOMAT AS-P SECURE BOOT (HW)

Gama: EcoStruxure Building Operation

nume scurt al dispozitivului: AS-P-S

marca de produs: Schneider Electric

Tip produs sau componenta: Controller

Compatibilitate gama: EcoStruxure Building Operation TB-ASP-W1 terminal base

EcoStruxure Building Operation TB-AS-W1 terminal base

tip conexiune integrata: USB 2.0 tip A

USB type mini B

servicii Web: TLS 1.0

HTTP server

Programmable scripts : alarm summaries, report management

serviciu de comunicare: SNMP network management

Notificare prin e-mail SMTP

SMTPS e-mail notification

Modbus TCP client

Modbus TCP server

nume procesor: Spear 320s

protocol port de comunicare: BACnet

Modbus TCP master - RS485 - 2-wire

Modbus TCP slave - RS485 - 2-wire

HTTPS 10/100BASE-T - RJ45

HTTP 10/100BASE-T - RJ45

LON - TP/FT-10

descriere memorie: RAM intern 512 MB

Flash 4 GB

capacitate procesor I/O limitator: 464 I/O, 29 modules

consum de curent: 400 mA la 24 V c.c.

montare produs: On base

Sina DIN

inaltime: 114 mm

latime: 90 mm

adancime: 64 mm

greutate neta: 321 g

material: ABS/PC

certificari produs: BTL

UE

cULus

FCC partea 15 clasa B

ICES-003

standarde: UL 94

UL 916

FCC CFR 47 part 15

grad de protectie IP: IP20

Intarziere flacara: UL94V0-5VB

temperatura ambientala de functionare: 0...50 °C

temperatura ambietala pentru depozitare: -20...70 °C

umiditate relativa: 0...95 %

Pret: 5.521,90 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/spacelogic-automat-as-p-secure-boot-hw>