



SCHNEIDER CUTIE JONCT. FARA FIR SI FARA BATERIE, 2 BUTOANE SIMPLE DE ACTIUNE

gama de produse: Harmony XB5R

Tip produs sau componenta: Emi??tor wireless ?i f??r? baterie

nume scurt al dispozitivului: XB5R

functionare contact: 2 simple action intrerupator cu revenire

material rama: Plastic

material inel de fixare: Plastic

diametrul de montaj: 22 mm

alcatuirea kitului: 1 set of caps

1 handy box

2 transmitter

2 push-button head diametru: 22 mm

2 fixing collars

forma a capului unitatii de semnalizare: Rotund

tip de operator: spring return push-button with transmitter

profil operator: Incastrat

informatii suplimentare operator: Set of caps

greutate neta: 0,2 kg

durabilitate mecanica: 1000000 cic

cursa de operare: 4,3 mm (curs? total?)

forta de actionare: 25 N C/O changing electrical state

rezistenta la socuri: 25 gn (durata = 6 ms) pentru 6000 shocks conformitate cu IEC 60068-2-27

30 gn (durata = 18 ms) pentru half sine wave acceleration conformitate cu IEC 60068-2-27

50 gn (durata = 11 ms) pentru half sine wave acceleration conformitate cu IEC 60068-2-27

rezistenta mecanica: Free fall resistance 1000 mm conformitate cu IEC 60068-2-32

protocol port de comunicare: Zigbee green power la 2,4 GHz

distanța maxima de sensibilitate: 100 m in free field

25 m transmitter in the handy box and receiver in a metal enclosure

300 m transmitter in the handy box, receiver in metal enclosure and use relay-antenna

time of acquisition: 2 ms

time of response: < 2 ms

transmission power: 3 mW

ambient temperature for storage: -40...70 °C

ambient temperature of operation: -25...55 °C

protection grade IP: IP65 conforming to SR EN 60529 (front face)

IP65 conforming to UL Tip 12 (front face)

protection grade IK: IK03 conforming to IEC 50102

relative humidity: 95 % at 70 °C f?r? condensation

vibration resistance: 5 gn (f= 11...500 Hz) conforming to IEC 60068-2-6

+/- 10 mm (f= 2...11 Hz) conforming to IEC 60068-2-6

electromagnetic compatibility: Test of immunity to electrostatic discharges - test level: 9 kV (in free air (in p?r?ile izolate)) conforming to IEC 61000-4-2

Test of immunity to electrostatic discharges - test level: 4 kV (on contact (on p?r?ile metalice)) conforming to IEC 61000-4-2

Sensitivity to electromagnetic fields - test level: 20 V/m (80...3000 MHz) conforming to IEC 61000-4-3

Sensitivity to electromagnetic fields - test level: 6 V/m (3000...6000 MHz, distance = 20 m) conforming to IEC 61000-4-3

radio agreement: RSS conforming to UL 508

ARIB T66 conforming to CSA C22.2 No 14

ICASA

ANATEL

FCC

standards: SR EN 60947-5-1

CSA C22.2 No 15

IEC 60947-1

UL 60947-1

product certification: C-Tick

CSA

BT 2006/95/EC

EAC

UL

CCC

directives: 2004/108/EC - electromagnetic compatibility?

1999/5/EC - R&TTE directive

Price: 792,54 LEI (TVA included)

Details online: <https://www.materialelectrice.ro/cutie-jonct-fara-fir-si-fara-baterie-2-butoane-simple-de-actiune>