



## SCHNEIDER SPACELOGIC, AUTOMAT AS-P-NL SECURE BOOT (HW), 2 PORTURI RS-485, 2 PORTURI 10/100 ETHERNET

Tip produs sau componenta: Network controller

timp rezerva: 10 days

Model: AS-P-NLS

certificari produs: BTL B-BC

Listat cUL

listat de UL

RCM

abatere ceas: +/- 52 s/month

culoare: Negru

serviciu de comunicare: TLS 1.0

nume scurt al dispozitivului: AS-P-NLS

Rezistenta la foc: UL94-5VB

puterea maxima consumata in W: 10 W

grad de protectie IP: IP20

mod de montare: DIN rail mount

frecventa retea electrica: 50 Hz

60 Hz

adancime: 64 mm

inaltime: 114 mm

greutate neta: 0,321 kg

latime: 90 mm

temperatura ambientala de functionare: 0...50 °C

temperatura ambietala pentru depozitare: -20...70 °C

tip memorie: 4 GB flash

512 MB RAM

Standarde: EN 61000-6-2

EN 50491-5-3  
EN 60730-1  
EN 60730-2-11  
EN 50491-3  
UL 916  
EN 50491-1  
EN 61000-6-3  
EN 50491-5-2  
FCC part 15 Subpart B class B  
Communication port support: Ethernet 10/100BASE-TX  
numarul portului: 2, tip conector: RJ45  
1, tip conector: USB device port Mini-B  
1, tip conector: USB host port type A  
2 RS485  
[Us] tensiune de alimentare nominala: 24 V c.a.  
24 V c.c.  
numarul maxim de dispozitive conectate: 464  
protocol port de comunicare: BACnet  
HTTP  
HTTPS  
Modbus TCP serial line master or slave  
TCP (Transmission Control Protocol)  
umiditate relativa: 0...95 % (RH, fara condensare)  
Pret: 4.970,57 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/spacelogic-automat-as-p-nl-secure-boot-hw-2-porturi-rs-485-2-porturi-10-100-ethernet>