



## SCHNEIDER MODUL DE CONVERSIE A FIBRELOR SINGLEMODE / CUPRU RJ45 2 CAI 100MB/S

gama de produse: Modicon X80

Tip produs sau componenta: Fibre optic repeater

tip de fibra optica: Single mode

tensiune nominala: 24 V

consum de curent: 140 mA tipic

200 mA maxim

functie disponibila: Hot swap

num?rul portului: 2 RJ45 cu 100BASE-TX conformitate cu IEEE 802.3u

2 fibre optice cu 100BASE-FX conformitate cu IEEE 802.3u

semnalizare locala: 1 LED (verde) for power supply status

1 LED (rosu) for error condition (ERR)

2 LED-uri (verde) for link status

2 LED-uri (verde) for fiber port state and activity

lungimea de unda: 1310 nm

distan?a de operare: 0...15000 m

atenuare maxima: -15...-8 dB (9/125  $\mu$ m)

timpul de crestere/cadere: 2,5 ns

sensibilitate receptor: - 31...- 8 dBm

marcaj: CE

latime: 32 mm

inaltime: 100 mm

adancime: 86 mm

greutate neta: 203 g

temperatura ambientala de functionare: 0...60  $^{\circ}$ C

temperatura ambietala pentru depozitare: -40...70  $^{\circ}$ C

umiditate relativa: 0...95 %

directive: 2014/35/EU - directiva joasa tensiune  
2014/30/EU - directiva de compatibilitate electromagnetica  
certificari produs: UE  
RCM  
CSA  
EAC  
Certificare navala  
UL  
standarde: IEC 61010-2-201  
IEC 61131-2  
UL 61010-2-201  
CSA C22.2 No 61010-2-201  
rigiditate dielectrica: 1400 V c.c. between field and bus  
500 V c.c. between channels  
grad de protectie IP: IP20  
altitudine de functionare: 0...4000 m  
Pret: 2.733,01 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modul-de-conversie-a-fibrelor-singlemode-cupru-rj45-2-cai-100mb-s>