



**SCHNEIDER UNITATE RACIRE CONECTABILA, MONTAJ PE LATERALUL
DULAPULUI, CLIMASYS CU, 800W, 2 POLI, 400/460V, 50/60HZ, IP55**

Gama: ClimaSys

nume produs: CU

Suport de montare: Lateral

Tip produs sau componenta: Cooling unit

Installation: Interior lateral

destinatie produs: Pentru carcasa

mod de montare: Cu suruburi

Supply Voltage: 380...415 V 2 faze 50 Hz EN/IEC

400/460 V +/- 6 % 2 faze 60 Hz UL

Rated Power: 900 W

putere de racire: 900 W 50/60 Hz L35-L35

700 W 50/60 Hz L35-L50

inaltime: 780 mm

latime: 345 mm

adancime: 215 mm

[In] curent nominal: 3 A

curentul de varf: 4 A

puterea consumata in W: 500 W la 50/60 Hz, L35-L35

530 W la 50/60 Hz, L35-L50

raportul de eficienta energetica: 1,8

tip de control: Controler electronic

gama de setare a temperaturii: 20...50 °C la 50/60 Hz

temperatura ambientala de utilizare: In cofret 20...50 °C la 50/60 Hz

Outside the enclosure 5...55 °C la 50/60 Hz

Noise level: 70 dB

presiune: 30 bar

Flow rate: Internal circuit 550 m³/h la 50/60 Hz

External circuit 850 m³/h la 50/60 Hz

greutate neta: 27,4 kg

tip de gaz de racire: R134a (0,120 kg)

Type of filter: Optional external circuit filter

Recommended circuit breaker protection: M9F23216

Thermal protection Recommended (fuse): 2 faze 15 A (T)

material: Otel

culoare: Gri (RAL 7035)

certificari produs: UL

IEC

directive: 2006/42/EC - machinery

2014/30/EU - directiva de compatibilitate electromagnetica

2011/65/EU - RoHS

standarde: EN/ISO 12100

EN 60335-1

EN 60335-2-40

EN 61000-3-2

EN 61000-3-3

EN 61000-6-2

EN 61000-6-3

SR EN IEC 63000:2019

EN 14511

grad de protectie IP: IP55 conformitate cu SR EN 60529 (on the internal circuit)

IP24 conformitate cu SR EN 60529 (on the external circuit)

Pret: 10.787,52 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/unitate-racire-conectabila-montaj-pe-lateralul-dulapului-climasys-cu-800w-2-poli-400-460v-50-60hz-ip55>