



TRACON CIL DE SIG-EVACUARE CU LED, REGIM PERMANENT/ NEPERMANENT
230V,50 HZ,5W,400LM, 20XLED,3H,3,2V/3200MAH,LIFEPO,IP65

Modalitate de montare: Wall surface mounted / ceiling surface mounting

Potrivit pentru etichetare: Sticker

Tip de indicator: Single-sided

Echipament de monitorizare: Test button

Sistem de cablare: Continuous circuit/emergency circuit

Sistemul de alimentare cu energie: Peripheral (individual battery)

Calitatea bateriei: Other

Lampa: LED not exchangeable

Cu lampa: Da

Culoare carcasa: White

Tip tensiune: AC

Tensiune nominala: 220 -240 V

Durata de viata evaluata L70/B50 la 25 de grade Celsius: 10.000 h

Grad de protectie (IP): IP65

Clasa de protectie: I

Temperatura ambientala evaluata conform IEC62722-2-1: -5 -40 °C

Putere sistem: 5 W

Flux luminos efectiv: 400 lm

Temperatura de culoare: 4.000 -4.000 K

Distanta de recunoastere: 22 m

Latime: 107 mm

Inaltime / adancime: 77 mm

Lungime: 345 mm

Numar de poli: 1

Valori:230V,50 Hz,5W,400lm, 20xLED,3h,3,2V/3200mAh,LiFePO,IP65

Pret: 270,06 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/cil-de-sig-evacuare-cu-led-regim-permanent-nepermanent-230v-50-hz-5w-400lm-20xled-3h-3-2v-3200mah-lifepo-ip65>