



**TRACON DISJUNCTOR CU PROTECTIE DIFERENTIALA, 2P, 2 MOD., CURBA B B13A,
30 MA, 10KA, A**

Numar de poli (total): 2
Numar poli protejati: 2
Tensiune nominala: 230 V
Tensiunea nominala de izolare U_i : 690 V
Impuls evaluat rezistenta voltaj U_{imp} : 4 kV
Curent nominal: 13 A
Curent nominal de defect: 0,03 A
Tip de curent de scurgere: A
Clasa de limitare curent: 3
Capacitate siguranta curent: 3 kA
Tip tensiune: AC
Frecventa: 50/60 Hz
Caracteristica declansare: B
Conexiune conductor neutru: Da
Temperatura mediu ambiant pe timp de functionare: -25 -40 °C
Latime in numar de distante modulare: 2
Instalare sub tencuiala: Da
Grad de protectie (IP): IP20
Sectiune transversala conductor masiv conectabil: 1,5 -25 mm²
Garantie: 1 an B13A, 30 mA, 10kA, A
Pret: 188,33 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctor-cu-protectie-diferentiala-2p-2-mod-curba-b-b13a-30-ma-10ka-a>