



**TRACON DISJUNCTOR CU PROTECTIE DIFERENTIALA, 4P, 4 MOD., CURBA B B20A,
300 MA, 10KA, A**

Numar de poli (total): 4

Numar poli protejati: 4

Tensiune nominala: 400 V

Tensiunea nominala de izolare U_i : 690 V

Impuls evaluat rezistenta voltaj U_{imp} : 4 kV

Curent nominal: 20 A

Curent nominal de defect: 0,3 A

Tip de curent de scurgere: A

Clasa de limitare curent: 3

Capacitate siguranta curent: 3 kA

Tip tensiune: AC

Frecventa: 50/60 Hz

Caracteristica declansare: B

Conexiune conductor neutru: Da

Temperatura mediu ambiant pe timp de functionare: -25 -40 °C

Latime in numar de distante modulare: 4

Instalare sub tencuiala: Da

Grad de protectie (IP): IP20

Sectiune transversala conductor masiv conectabil: 1,5 -25 mm²

Garantie: 1 an B20A, 300 mA, 10kA, A

Pret: 482,84 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctor-cu-protectie-diferentiala-4p-4-mod-curba-b-b20a-300-ma-10ka-a>