



## **TRACON DISJUNCTOR CU PROTECTIE DIFERENTIALA, 4P, 4 MOD., CURBA B B40A, 300 MA, 10KA, A**

Numar de poli (total): 4  
Numar poli protejati: 4  
Tensiune nominala: 400 V  
Tensiunea nominala de izolare Ui: 690 V  
Impuls evaluat rezistenta voltaj Uimp: 4 kV  
Curent nominal: 40 A  
Curent nominal de defect: 0,3 A  
Tip de curent de scurgere: A  
Clasa de limitare curent: 3  
Capacitate siguranta curent: 3 kA  
Tip tensiune: AC  
Frecventa: 50/60 Hz  
Caracteristica declansare: B  
Conexiune conductor neutru: Da  
Temperatura mediu ambiant pe timp de functionare: -25 -40 °C  
Latime in numar de distante modulare: 4  
Instalare sub tencuiala: Da  
Grad de protectie (IP): IP20  
Sectiune transversala conductor masiv conectabil: 1,5 -25 mm<sup>2</sup>  
Garantie: 1 an B40A, 300 mA, 10kA, A  
Pret: 482,84 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctor-cu-protectie-diferentiala-4p-4-mod-curba-b-b40a-300-ma-10ka-a>