



**TRACON DISJUNCTOR CU PROTECTIE DIFERENTIALA, 4P, 4 MOD., CURBA C C16A,
300 MA, 10KA, A**

Numar de poli (total): 4
Numar poli protejati: 4
Tensiune nominala: 400 V
Tensiunea nominala de izolare U_i : 690 V
Impuls evaluat rezistenta voltaj U_{imp} : 4 kV
Curent nominal: 16 A
Curent nominal de defect: 0,3 A
Tip de curent de scurgere: A
Clasa de limitare curent: 3
Capacitate siguranta curent: 3 kA
Tip tensiune: AC
Frecventa: 50/60 Hz
Caracteristica declansare: C
Conexiune conductor neutru: Da
Temperatura mediu ambiant pe timp de functionare: -25 -40 °C
Latime in numar de distante modulare: 4
Instalare sub tencuiala: Da
Grad de protectie (IP): IP20
Sectiune transversala conductor masiv conectabil: 1,5 -25 mm²
Garantie: 1 an C16A, 300 mA, 10kA, A
Pret: 482,84 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctor-cu-protectie-diferentiala-4p-4-mod-curba-c-c16a-300-ma-10ka-a>